

LUBRICANTS.
TECHNOLOGY.
PEOPLE.



Lubricants for Coastal

MOVING YOUR WORLD



MOVING YOUR WORLD with lubrication solutions designed for Australia's Coastal applications

The ocean is a vulnerable environment. Shipping companies and others with the sea as their workplace are under increasing pressure in the form of ever stricter environmental legislation. At FUCHS, we have long had a close working relationship with manufacturers and the shipbuilding industry, and we know the conditions under which they work. This enables us to offer a complete range of lubricant products for our markets that both fulfil the demanding specifications of the shipping industry and meet the most stringent environmental requirements in Australia and New Zealand.

We always use quality raw materials and our entire business is certified in accordance with the environmental and quality standards ISO

9001:2015 and ISO 14001:2015. Our customers can always feel safe in the knowledge that we deliver what we promise.

Within coastal marine applications, there are many areas which require lubrication. This includes both 'on board' and 'on shore' as many businesses have operations in both areas. The products listed here should be considered a broad general offer for this sector, which would cater to most applications. FUCHS has an exceptionally large range of products to choose from and far too many to list in any brochure. Additional products can be sought upon application. Please contact your sales contact for any additional requirements.



Contents

FUCHS CORPORATE

FUCHS Coastal Industry Overview	2
About FUCHS	4

LUBRICANT RANGES

Diesel Engine Oils	5
Engine Coolants	8
Transmission Oils	11
Gear Oils	12
Hydraulic Oils	14
Compressor Oils	15
Refrigeration Oils	16
Anticorrosives	16
Wire Rope	17
Greases	17
Food Grade Products	18
Biodegradable Products	18

About FUCHS

FUCHS is a global brand with a German heritage that has developed, produced and sold lubricants and related specialties for more than 90 years. Comprising 71 operating companies (as of December 31, 2024) and more than 6,500 employees worldwide, the FUCHS Group is a leading independent supplier of lubricants.

The FUCHS product program comprises more than 11,000 products covering 25+ different industries including:

- **Automotive Lubricants**
- **Mining Lubricants**
- **Industrial Lubricants**
- **Lubricating Greases**
- **Metal Processing Lubricants**
- **Food Processing Lubricants**
- **Special Application Lubricants; and**
- **Services**

Along with its Sunshine (VIC) facility, FUCHS Lubricants (Australasia) Pty. Ltd. produces a selection of its products within its 25,000 square metre purpose built Beresfield (Newcastle, NSW) plant.

Keeping in line with its core values, both FUCHS facilities manufacture products using high-quality materials and cutting-edge technology whilst also adhering to industry leading environmental and manufacturing policies and requirements.

Working closely with its customers, FUCHS develops holistic, innovative and custom-made solutions for a variety of applications.

And while that means the company is perfectly positioned to respond to the immediate needs of its customers - particularly in emergency situations - it also proudly means jobs for Australians.

As a lubricant manufacturer, FUCHS stands for performance, sustainability, safety, reliability and efficiency.

FUCHS LUBRICANTS. MOVING YOUR WORLD.

Wayne Hoiles

Regional Vice President
Australasia, India, Southeast Asia, Japan & South Korea

FUCHS Lubricants (Australasia) Pty. Ltd. operate with SAI Global certified systems along with ISO IATF 16949 certification, focused on high quality outcomes & mitigation of risk.



DIESEL ENGINE OILS

TITAN CARGO SAE 15W-40

Many recent era vessels utilise land based engines which require specification CK-4 or Original Equipment Manufacturer (OEM) approval.

TITAN Cargo SAE 15W-40 features a CK-4 specification which not only meets today's stringent emission requirements but also the engine performance of modern OEMs. It is also compatible with earlier specifications, making it an excellent all fleet product and reducing the risk of mis-application.

Specifications	Approvals	Recommendations
- ACEA E11/E7 - API CK-4/CJ-4/SN - CAT ECF-3 - JASO DH-2	- ALLISON TES 439 - DETROIT DIESEL 93K222 - DEUTZ DQC III-18 LA - DTFR 15C100 - FORD M2C171-F1 - MACK EOS-4.5 - MAN M 3775 - MTU DDC TYPE 2.1 - RENAULT RLD-3 - VOLVO VDS-4.5	- ACEA E9 - MAN M 3575 - MB 228.31 - RENAULT RLD-4

Pack Sizes	5L	10L	20L	205L	1000L
Material No.	602290977	602290984	602291004	602291035	602291028
Part No.	4890005	4890010	4890020	4890205	48901000

TITAN TRUCK PLUS SAE 15W-40

Some older era vessels are fitted with land based engines requiring specification CI-4.

TITAN TRUCK PLUS SAE 15W-40 is a super-long-term all season engine oil of the UHPD category, and is well suited for this application.

Specifications	Approvals	Recommendations
- ACEA E7 - API CI-4/SL - CAT ECF-1-a/ECF-2 - GLOBAL DHD-1	- CUMMINS CES 20076 - CUMMINS CES 20077 - CUMMINS CES 20078 - DETROIT DIESEL 93K215 - DEUTZ DQC III-18 - DTFR 15B110 - MACK EO-N - MTU DDC TYPE 2 - RENAULT RLD / RLD-2 - VOLVO VDS-3	- ALLISON C-4 - CASE MS 1121 - CAT TO-2 - CNH MAT 3507 - CUMMINS CES 20071/2 - IVECO 18-1804 CLASSE T2 E7 - MAN M 3275-1 - MB 228.3 - NH 330 H

Pack Sizes	5L	10L	20L	205L	1000L
Material No.	602285867	602285874	602285898	602299062	602071446
Part No.	4191005	4191010	4191020	4191205	41911000

DIESEL ENGINE OILS

TITAN MARWAY 1040 SAE 40

TITAN MARWAY is a high performance marine engine oil for high and medium speed diesel engines. It is specially developed for engines operating under harsh conditions. This is a traditional Marine specification.

Specifications SAE J300: SAE 40	Approvals - MAN DIESEL & TURBO - ROLLS ROYCE-BERGEN - WÄRTSILÄ	Recommendations MIL L-2104 D
Pack Sizes	205L	1000L
Material No.	602290441	602290434

TITAN CARGO MC 10W-40

TITAN CARGO MC SAE 10W-40 is an ultra high performance engine oil, it carries MAN M 3277 approval, as specified in some vessels, along with other key specifications.

Specifications ■ ACEA E7/E4 ■ API CI-4 ■ GLOBAL DHD-1		Approvals ■ CUMMINS CES 20077/8 ■ DETROIT DIESEL 93K215 ■ DEUTZ DQC III-10 ■ MACK EO-M PLUS/EO-N ■ MAN M 3277 ■ MB-APPROVAL 228.5 ■ MTU DDC TYPE 3 ■ RENAULT RXD/RLD-2 ■ SCANIA LDF-2 ■ VOLVO VDS-3		Recommendations ■ IVECO 18-1804 ■ SDFG OM-1901A	
Pack Sizes	20L	205L	1000L		
Material No.	602284082	602284099	602298591		

TITAN UNIVERSAL XT 30

TITAN UNIVERSAL XT 30 is a high performance monograde engine oil for diesel and gasoline engines. It meets API CD specifications and is often used for onboard stationary engines.

Specifications ■ N/A		Approvals ■ N/A		Recommendations ■ API SF/CD	
Pack Sizes	1L	5L	20L	205L	
Material No.	602282934	602282941	602282958	602282965	

TITAN UNIVERSAL HD 40

TITAN UNIVERSAL HD 40 is an older specification monograde SAE 40 meeting API CF-4 specifications. It is often used in onboard stationary engines.

Specifications

- N/A

Approvals

- MTU - TITAN UNIVERSAL HD SAE 40
- DEUTZ DQC I-02
- MB-APPROVAL 228.2
- MB-APPROVAL 235.12
- MTU DDC TYPE 2
- ZF TE-ML 04B (ZF001190)

Recommendations

- ACEA E2
- API CF-2/CF-4/SG
- MIL-L-2104 D
- ALLISON C-4
- CAT TO-2
- MAN 270
- ZF TE-ML 02C

Pack Sizes	20L	205L	1000L
Material No.	602282972	600638603	602236661

ENGINE COOLANTS

FRICOFIN 50

FRICOFIN 50 is a premium performance coolant pre-mix based on monoethylene glycol.

Free of nitrites, amines and phosphates with hybrid technology. It offers frost protection down to -37°C. MAN specification has made this popular in marine applications.

Specifications	Approvals	Recommendations
■ AFNOR NF R 15-601 TYPE 3 ■ ASTM D 3306 TYPE III ■ ASTM D 4985 ■ BS 6580:2010 ■ SAE J814	■ DEUTZ DQC CA-14 ■ DTFR 29D100 (MB 326.0) ■ MAN 324 TYPE NF ■ MTU MTL 5048	■ BMW LC-87 (BMW GS 94000) ■ DAF 74001 ■ GM 1899-M ■ INNIO JENBACHER TA 1000-0201 ■ LIEBHERR TLV 035/TLV 23009 A ■ MAN 324 TYPE NF PRITARDER ■ CAT / MWM TR 0199-99-2091 ■ OPEL/GM B 040 0240 ■ PN-C 40007:2000 ■ VOITH TURBO 172.00225010 ■ VW TL 774-C (G11)

Pack Sizes	20L	205L	1000L
Material No.	602286697	602286710	602286703
Part No.	4312020	4312205	43121000

FRICOFIN DP 50

BlueEV
TECHNOLOGY

FRICOFIN DP 50 is an ultra-high performance coolant pre-mix based on monoethylene glycol. It offers frost protection down to -35°C.

It is based on Si-OAT technology, which is among the latest technology on the market. Also popular as a multifleet product (subject to technical review).

Specifications	Approvals	Recommendations
■ AFNOR NF R 15-601 TYPE 3 ■ ASTM D 3306 TYPE III ■ ASTM D 4985 ■ BS 6580:2010 ■ SAE J814	■ CUMMINS CES 14603 ■ DEUTZ DQC CC-14 ■ DETROIT DIESEL 93K217 ■ DTFR 29D120 (former MB 326.5) ■ MAN 324 TYPE Si-OAT ■ MB 326.6 ■ MTU MTL 5048 ■ VW TL 774-G (G12++) ■ VOITH (172.00225040 – Type Si-OAT)	■ ASTM D 6210 TYPE III ■ IVECO 18-1830 ■ MB 326.5 ■ PN-C 40007:2000 ■ SCANIA TB 1451 ■ VW TL 774-J (G13)

Pack Sizes	20L	205L	1000L
Material No.	602291127	602291141	602314284
Part No.	4898020	4898205	48981000

FRICOFIN MP 50

FRICOFIN MP 50 is a premium performance coolant pre-mix based on monoethylene glycol. It offers freezing protection down to -37°C.

Specifications ■ ASTM D2895 ■ ASTM D3306-20 TYPE III ■ ASTM D 4985 ■ AS/NZS 2108:2004 TYPE A ■ BS 6580:2010 ■ SAE J1034	Approvals ■ N/A	Recommendations ■ CASE MS 1710 ■ DETROIT DIESEL 7SE298 ■ FORD ESE-M97B44-A ■ FORD ESE-M97B18-C ■ FORD WSS M97B51-A1 ■ GM 1825M/GM 1899M ■ GM HN 2217 ■ JASO M325 ■ JIS K2234 ■ MAN 324 TYPE SNF ■ MAZDA MEZ MN 121 D ■ MB 326.3/DTFR 29D120 ■ NEW HOLLAND WSN-M97B18-D ■ SAAB 690 1599 ■ TMC RP 329	
Pack Sizes	20L	205L	1000L
Material No.	602302762	602302779	602302847
Part No.	5770020	5770205	57701000

FRICOFIN CV 50

FRICOFIN CV 50 is a prediluted, ready-to-use, long life antifreeze, antiboil coolant and corrosion inhibitor.

It is free of borates, nitrites, amines, silicates and phosphates and is formulated using highly efficient x-OAT. It is often favoured by Asian based manufacturers.

Specifications ■ AFNOR NF R15-601 ■ ASTM D2895 ■ ASTM D3306-20 TYPE III ■ ASTM D 4985 ■ AS/NZS 2108:2004 TYPE A ■ BS 6580:2010 ■ China GB 29743-2013 ■ FVV Heft R443 ■ SAE J1034	Approvals ■ N/A	Recommendations ■ BAIC GROUP FOTON Q-FPT 2313005-2013 ■ Bergen Engines 2.13.01 ■ CAT EC-1 ■ CNH MAT 3624/CNH MAT 3724 ■ CUMMINS CES 14603, CES 14439 ■ DAF 74002 ■ DETROIT DIESEL 93K217 ■ DEUTZ DQC CB-14 ■ FORD WSS-M97B44-D ■ GM 6277M/GMW 3240/GMW 18270 ■ Jaguar/Land Rover STJLR.03.5212 ■ JASO M325 ■ JCB 00088 ■ JIS K2234 ■ Komatsu 07.892 (2017) ■ LIEBHERR MD 1-36-130 ■ MAN 324 TYPE SNF ■ MAN ENERGY SOLUTIONS CW 28 33 ■ MB 326.3/DTFR 29D120 ■ MTU MTL 5048 ■ Toyota TSK2601G ■ UNE 26-361-88/1 ■ VOLVO COOLANT VCS (STD 418-0001) ■ VOLVO COOLANT VCS-2 (STD 408-0007) ■ VOLVO COOLANT XLC (STD 418-0005) ■ VW TL774D/F		
Pack Sizes	5L	20L	205L	1000L
Material No.	602708595	602302786	602302793	602302854
Part No.	5771005	5771020	5771205	57711000

ENGINE COOLANTS

FRICOFIN HDD-PG 50

FRICOFIN HDD-PG 50 is a long-life, ready-to-use coolant based on propylene glycol. Utilising similar HOAT technology to the FRICOFIN MP50, the FRICOFIN HDD-PG 50 offers lower toxicity and greater environmental sensitivity, particularly well suited to marine environments.

Specifications - ASTM D 3306 - ASTM D 6210 Type IV-FF - ASTM D 7583 - TMC RP 330	Approvals N/A	Recommendations - CUMMINS CES 14603 - DETROIT DIESEL 7SE 298 - KENWORTH R026-170-97 - MACK 014GS17004 - MAN 324 TYPE N - MTU MTL 5048 - NEW HOLLAND (WSN-M97B18-D)
Pack Sizes	20L	1000L
Material No.	602287878	602287885
Part No.	4519020	45191000

FRICOFIN DCI PREMIX

FRICOFIN DCI PREMIX is water-based, prediluted, ready to use, long life coolant and corrosion inhibitor.

FRICOFIN DCI is a glycol free coolant that does not contain antifreeze or antiboil characteristics, it is used for marine engines where glycol-based antifreeze coolants are not required.

Specifications - ASTM D-3306 / D-4985 - AS/NZS 2108:2004 Type B - SAE J1034 / J1941	Approvals N/A	Recommendations - CATERPILLAR MARINE POWER SYSTEMS (MAK), A4.05.09.01 - DETROIT DIESEL - DEUTZ TR 0199-99-1115 - MWM TR 0199-99-2091 - GEC ALSTHOM - HYUNDAI - LIEBHERR MD 1-36-130 - MAN DIESEL B&W - MAN 248 - MENAG - MTU MTL 5049 - NEW SULZER DIESEL - ULSTEIN BERGEN 2.13.01 - WARTSILA, WAUKESKA, YANMAR
Pack Sizes	1000L	
Material No.	800466969	

TRANSMISSION OILS

TITAN ATF 4400

TITAN ATF 4400 is an ultra high performance and specification listed ATF for use where such a fluid is required. .

Specifications JASO M315 TYPE 1A		Approvals N/A	Recommendations - BMW MINI 83 22 0 402 413/83 22 7 542 290 - CHRYSLER MS7176E/9602 (ATF +3/+4) - DAIHATSU ALUMIX ATF MULTI - DEXRON III - FIAT 9.55550-AV1/AV4 - FORD M2C924-A/M2C922-A1 - FORD MERCON - GM 9986195 - HONDA ATF Z-I - HYUNDAI SP III - ISUZU BESCO ATF-II/ATF-III		
Pack Sizes	1L	4L	20L	60L	205L
Material No.	602298430	602291509	602291516	602291523	600700911
Part No.	4935001	4935004	4935020	4935060	4935205

TITAN UTTO TO-4 30

TITAN UTTO TO-4 30 is a high performance, specification listed, multi-functional, off-highway UTTO for use where such a fluid is required.

Specifications ■ API GL-4 ■ CATERPILLAR TO-4		Approvals ■ ZF TE-ML 03C (For SAE 10W, SAE 30) ■ ZF TE-ML 07F (SAE 30 only)		Recommendations ■ ALLISON TES-439 (SAE 30 only) ■ KOMATSU KES 07.868.1	
Pack Sizes		20L	205L	1000L	
Material No.		602282828	600904333	602282842	
Part No.		2157020	2157205	21571000	

GEAR OILS

RENOLIN CLP PLUS SERIES

RENOLIN CLP PLUS is a special industrial gear oil based on high-quality base oils and synergistically acting additives to improve ageing resistance, load carrying capacity and wear protection.

RENOLIN CLP products fulfill CLP classification, with additional capabilities against salt/water ingress. This product is capable of accepting up to 5% salt/fresh water and maintaining all aspects of operation. It's ideally suited to marine applications where moisture ingress potential is high.

Specifications - DIN 51 517-3: CLP - ISO 6743-6 & ISO 12925-1:CKC/CKD - AGMA 9005/E02:EP		Approvals Ask your FUCHS Sales Representative		Recommendations Ask your FUCHS Sales Representative	
RENOLIN CLP 320 PLUS	10L	20L	205L	1000L	
Material No.	602289476	602289483	602270207	602757760	
Part No.	4699011	4699020	4699205	46991000	
RENOLIN CLP 460 PLUS	10L	20L	20L	1000L	
Material No.	602289513	602289520	602289544	602289537	
Part No.	4703011	4703020	4703205	47031000	

RENOLIN UNISYN CLP SERIES

RENOLIN UNISYN CLP Series oils lower friction, reduce wear and increase the efficiency of machine components.

This fully synthetic industrial gear oil meets CLP classification and offers longer drain.

Specifications - DIN 51 517-3: CLP - ISO 6743-6 & ISO 12925-1: CKC/CKD/CKE - AGMA 9005/E02:EP - AIST 224 - David Brown S1 53.101 - FAG Requirements: FAG-FE8-Test: stage 1-4 pass - SKF requirements: pass (100°C-test)		Approvals Ask your FUCHS Sales Representative		Recommendations Ask your FUCHS Sales Representative	
RENOLIN UNISYN CLP 220	20L	205L	205L		
Material No.	602281586	602281609	602281593		
Part No.	1916020	1916205	1916205		
RENOLIN UNISYN CLP 320	20L	205L	1000L		
Material No.	602281623	602281654	602281647		
Part No.	1917020	1917205	19171000		

RENOLIN CLP SERIES

The RENOLIN CLP Series of gear oils contains carefully selected base oil and matched additives to protect machinery from undue wear. This mineral oil meets CLP classification.

Specifications

- DIN 51 517-3 (2011): CLP
- ISO 6743-6: CKC/CKD
- ISO 12925-1: CKC/CKD
- AIST 224
- AGMA 9005/E02:EP
- David Brown S1 53.101

Approvals

- Ask your FUCHS Sales Representative

Recommendations

- Ask your FUCHS Sales Representative

RENOLIN CLP 68	20L	205L	1000L
Material No.	602281845	602294548	602294548
Part No.	1926020	1926205	19261000
RENOLIN CLP 100	20L	205L	
Material No.	602281661	600634308	
Part No.	1918020	1918205	
RENOLIN CLP 150	20L	205L	1000L
Material No.	602281678	600634315	602281692
Part No.	1920020	1920205	19201000
RENOLIN CLP 220	20L	205L	1000L
Material No.	602281722	600634322	602281746
Part No.	1921020	1921205	19211000
RENOLIN CLP 320	20L	205L	1000L
Material No.	602281760	600634339	602281784
Part No.	1924020	1924205	19241000
RENOLIN CLP 460	20L	205L	1000L
Material No.	602281807	600634346	601353710
Part No.	1925020	1925205	19251000

HYDRAULIC OILS

RENOLIN B 15 HVI

RENOLIN B 15 HVI is a mineral ISO 15 hydraulic oil with exceptionally high viscosity index meaning very stable operation of hydraulic systems over a wide temperature band. This particular grade is often used in cool room applications.

Specifications

- DIN 51 524-3 : HVLP
- ISO 6743-4: HV
- ISO 11158
- DENISON HFO
- BOSCH REXROTH
- VICKERS
- US STEEL
- CINCINNATI MILACRON

Approvals

- N/A

Recommendations

- N/A

Pack Sizes	20L	1000L
Material No.	602287878	602287885

RENOLIN B HVI PLUS RANGE

RENOLIN B HVI PLUS is a range of premium hydraulic oils with exceptionally high viscosity index (HVI), meaning very stable operation of hydraulic systems over a wide temperature band.

Specifications

- Bosch Rexroth
- Cincinnati Milacron
- Denison HFO
- DIN 51 524-3, HVLP
- Ford M-6C32
- ISO 6743-4
- Racine, variable volume vane pumps
- Sauer Danfoss (46 only)
- US Steel 126, 127
- VICKERS I 286-S, M 2950-S

RENOLIN B 32 HVI PLUS	5L	20L	205L	
Material No.	602281111	602281128	602281135	
Part No.	1695005	1695020	1695205	
RENOLIN B 46 HVI PLUS	5L	20L	205L	1000L
Material No.	602281142	602281159	602281173	602281166
Part No.	1696005	1696020	1696205	16961000
RENOLIN B 68 HVI PLUS	5L	20L	205L	1000L
Material No.	602281180	602281197	600627508	602281210
Part No.	1697005	1697020	1697205	16971000

RENOLIN B PLUS RANGE

RENOLIN B PLUS is a range of premium hydraulic oil, meeting HLP specification.

Specifications

- AFNOR E48-603
- Bosch Rexroth (46 only)
- Cincinnati Milacron P-68, P-69, P-70
- Denison HF-1, HF-2, HF-0
- DIN 51524-2: HLP

RENOLIN B 46 PLUS	5L	20L	205L	1000L
Material No.	602280763	602280770	601447860	602280794
Part No.	1667005	1667020	1667205	16671000
RENOLIN B 68 PLUS	5L	20L	205L	1000L
Material No.	602280817	602280824	601447891	602280848
Part No.	1668005	1668020	1668205	16681000

COMPRESSOR OILS

RENOLIN SYNAIR 46

RENOLIN SYNAIR 46 is a high performance synthetic air compressor fluid, utilising the latest technology popular with compressor manufacturers. The glycol/ester based formula also offers biodegradability.

Pack Sizes	10L
Material No.	602297624
Part No.	4328010

RENOLIN UNISYN OL SERIES

RENOLIN UNISYN OL is range of full synthetic compressor oils meeting typical compressor requirements and offering longer drain.

RENOLIN UNISYN OL 46	20L	205L	1000L
Material No.	602297662	602297679	602297655
Part No.	4619020	4619205	46191000
RENOLIN UNISYN OL 68	20L	205L	1000L
Material No.	602297686	602297693	602297709
Part No.	4677020	4677205	46771000

RENAIR SERIES

RENAIR oils are compressor oils belnded from solvent refined mineral oils and containing additives to reduce wear and oxidation, and meeting typical compressor requirements.

RENAIR 46	20L	205L	1000L
Material No.	602281494	602281524	602281517
Part No.	1910020	1910205	19101000
RENAIR 68	20L	205L	1000L
Material No.	602281531	602281562	602281555
Part No.	1911020	1911205	19111000

REFRIGERATION OILS

RENISO TRITON SEZ

RENISO TRITON SEZ is a range of fully-synthetic, ester-based refrigeration oils for HFC, FC and HFO refrigerants providing broad refrigerant coverage for onboard freezer and refrigeration requirements.

Specifications

- DIN 51503-1 Groups KC, KD, KE
- NSF H2 - registration number 146752

RENISO TRITON SEZ 32		5L
Material No.		602297303
RENISO TRITON SEZ 68		5L
Material No.		02297327
RENISO TRITON SEZ 170	1L	5L
Material No.	602297242	602297259

ANTICORROSIVES

ANTICORIT DFW

ANTICORIT DFW is a specialised dewatering fluid with waxy film in a solvent carrier fluid, providing moderate protection.

Pack Sizes	4L	20L	205L
Material No.	602279927	602279934	602279941

ANTICORIT BW 366

ANTICORIT BW 366 is a highly concentrated dewatering fluid with heavy waxy film in a solvent carrier fluid, providing extreme protection.

Pack Sizes	9.17L
Material No.	602295019

WIRE ROPE

RENOLIT MT WRC 0

RENOLIT MT WRC 0 is an excellent penetrating and protecting wire rope compound, ensuring all wire rope strands are protected from corrosion enabling longer life and confidence of rope integrity.

Pack Sizes	20Kg	180Kg
Material No.	602800053	602800046

GREASES

RENOLIT XTB 2

RENOLIT XTB 2 is a multipurpose, lithium complex grease with excellent ability.

Pack Sizes	450g	500g	2.5kg	20kg	55kg	180kg
Material No.	602285461	602285478	602285386	602285409	602285416	602285430
Part No.	4095450	4095500	40950025	4095020	4095055	4095180

RENOLIT CXI 2

RENOLIT CXI 2 is a heavy duty, water resistant calcium complex grease, ideal for marine applications.

Pack Sizes	450g	20kg	55kg	180kg
Material No.	602316523	602285669	602285676	602299314
Part No.	4143450	4134020	4143055	4143180

FOOD GRADE PRODUCTS

CASSIDA GREASE LTS 1

CASSIDA GREASE LTS 1 is a food grade NGLI 1 full synthetic grease with excellent low temp performance. Suitable for onboard and on shore processing applications.

Specifications N/A		Approvals - Allergy Statement - Approval - NZFS MPI Declaration - Hazardous Declaration - Declaration - NZ - HALAL Approval - Cassida Greases - HALAL Approval - FUCHS LUBRITECH	Recommendations N/A
Pack Sizes	400g		0.47L
Material No.	600759971		602295798

CASSIDA GREASE EPS 2

CASSIDA GREASE EPS 2 is a food grade NGLI 2 full synthetic, extreme pressure grease, suitable for onboard and on shore processing applications.

Specifications N/A		Approvals - Approval - NZFS MPI - Hazardous Declaration - Declaration - NZ - HALAL Approval - Cassida Greases - HALAL Approval - FUCHS LUBRITECH		Recommendations N/A		
Pack Sizes	0.005L	0.25L	0.38L	0.5L	19L	170L
Material No.	602285775	602275998	602295682	602295699	602295668	602295675

CASSIDA CHAIN OIL LT SPRAY

CASSIDA CHAIN OIL LT SPRAY is a food grade full synthetic chain lube in a spray offer, with excellent low temperature performance. Suitable for onboard and on shore processing applications.

Pack Sizes	0.4L
Material No.	602295149

CASSIDA CHAIN OIL 1500 SPRAY

CASSIDA CHAIN OIL 1500 SPRAY is a food grade full synthetic chain lube in a spray offer, with excellent adhesion performance. Suitable for onboard and on shore processing applications.

Pack Sizes	0.4L
Material No.	602295095

BIODEGRADABLE PRODUCTS

PLANTOHYD 46

PLANTOHYD 46 is a biodegradable hydraulic fluid, based on renewable resources and >60% biodegradable according to OECD 301B.

PACK SIZES	20L	205L
Material No.	602283740	602283764
Part No.	2877020	2877205

PLANTOHYD 68

PLANTOHYD 68 is a biodegradable hydraulic fluid, based on renewable resources and >60% biodegradable according to OECD 301B.

PACK SIZES	20L	205L	1000L
Material No.	602281289	602281319	602281296
Part No.	1804020	1804205	18041000

PLANTOFLUX SE 68

PLANTOFLUX SE 68 is a fire-resistant hydraulic oil based on synthetic esters and >60% biodegradable according to OECD 301B. It is classified as HFDU fire resistant.

PACK SIZES	205L	1000L
Material No.	602187406	602752017

PLANTOGear 320S

PLANTOGear 320S gear oil is based on synthetic esters and >60% biodegradable according to OECD 301B. Also suitable as a stern tube lube.

PACK SIZES	20L
Material No.	600625689

PLANTOGEL ECO 2N

PLANTOGEL ECO 2N is a NGLI 2 grade grease based on renewable resources and >60% biodegradable according to OECD 301B.

Specifications ISO-L-XB(F)BEA 2	Approvals EU Ecolabel DE/027/273	Recommendations N/A
PACK SIZES	18L	
Material No.	602297136	

FUCHS Oil Selector App



MOVING YOUR WORLD by finding the right oil EASIER!

Finding the correct FUCHS Lubricants product for a vehicle has never been easier with FUCHS Oil Selector App!

Simply search for '**NetLube FUCHS Australia**' at the App Store to download and enter your vehicle into the search bar to get all the information you'll need to choose the most suitable FUCHS Lubricant for the job!



German Technology, Australasian Commitment.

95% of products sold in Australia and New Zealand
are manufactured in Australia

1700 lubricants and related specialties

290 employees

2 world class production plants and laboratories being the
only Australian manufacturer to produce lubricants, coolants,
greases and additives

LUBRICANTS.
TECHNOLOGY.
PEOPLE.



FUCHS LUBRICANTS AUSTRALASIA

Head Office Melbourne

49 McIntyre Road, Sunshine Victoria 3020

Phone AUS: 1800 1800 13 Phone NZ: 0800 382 476

Email: contact-industrial.au@fuchs.com

fuchs.com.au

This brochure is accurate in information to the FUCHS Lubricants product range at the time of printing. FUCHS Lubricants reserves the right to make changes at any time without notice. Details also available from your FUCHS Lubricants representative.
Copyright FUCHS Lubricants (Australasia) Pty Ltd. January 2026.