

Alert Turbin Test

Inden for rammerne af vores tjeneste Advisor Alert tilbyder vi en færdig analysepakke for turbineolier. Alert Turbine Test er en del af en systematiseret vedligeholdelse, hvor du hurtigt får en indikation af, om noget ikke er, som det skal være.

Det er let at komme i gang med Alert Turbine Test. Du bestiller prøvepakken samme sted, som du bestiller dine andre smøremiddelprodukter. Første gang, du anvender Alert, registrerer du det system, du ønsker at sende prøver fra, og derefter kan du nemt udskrive færdige analyseetiketter via vores hjemmeside. Efter ca en uge får du svar på dine prøver, og via vores hjemmeside har du adgang til alle rapporter.

Bestilling

- Artikelnummer 940057225.
- Skulle du have spørgsmål, kan du altid henvende dig til kundeservice på telefon 32 46 30 00 eller e-mail fse-bestil@fuchs.com.

Nedenfor finder du en oversigt over, hvilke analyser der indgår i Alert Turbine Test.

Test	Method	Turbine B
Air Release @ 50°C	ASTM D3427	X
Appearance	In-house	X
Water Separation @ 54°C	ASTM D1401	X
Ferrous Debris by PQ Particle Quantifier	In-house	X
Foaming Characteristics @ 24° C (Seq I)	IP 146	X
ISO Particle Counting	ISO 4406	X
Kinematic Viscosity @ 40 and 100°C	ASTM D7279	X
Rotating Pressure Vessel Oxidation Test (RPVOT)	ASTM D2272	X
RULER	ASTM D6971	X
Neutralization number	IP 139/ASTM D974	X
Varnish Potential by MPC	ASTM D7843	X
Water Content by Karl Fischer	ASTM D6304	X
Wear Metals And Contamination Elements by ICP	ASTM D5185	X