



LUBRICANTS FOR MITSUBISHI PASSENGER CARS



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for Mitsubishi.

Product name	Description	Specifications	Approvals	FUCHS Recommendations
Engine Oils				
TITAN GT1 FLEX 5 SAE 0W-20 	Premium Performance Engine Oil with new XTL®-Technology in path-breaking viscosity class. Specially designed for highly stressed downsized engines with maximum power output, for extreme fuel-economy characteristics and reduced CO ₂ emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves.	ACEA C5 API SN PLUS RC API SP RC ILSAC GF-5 ILSAC GF-6A	–	–
TITAN GT1 FLEX C23 SAE 5W-30	Premium Performance, extreme fuel-economy engine oil with optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals.	ACEA C2/C3 API SP	–	–
TITAN GT1 PRO C-3 SAE 5W-30 	Premium Performance, extreme fuel-economy engine oil with new XTL®-Technology for optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals.	ACEA C3 API SN	VW 504 00/ 507 00	–
TITAN GT1 PRO C-1 SAE 5W-30	Premium Performance, extreme fuel-economy engine oil for modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for vehicles with exhaust after treatment and turbocharger. Optimum cold starting, lower oil consumption and minimized exhaust emissions.	ACEA C1	–	JASO DL-1
TITAN GT1 PRO 2290 SAE 5W-30	Premium Performance, extreme fuel-economy engine oil for modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for PSA vehicles with exhaust after treatment and turbocharger. Optimum cold starting, lower oil consumption and minimized exhaust emissions.	ACEA C2	PSA B71 2290	–
TITAN Supersyn LONGLIFE SAE 5W-40	Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption.	ACEA A3/B4 API SN/SM	PSA B71 2296	API CF
TITAN Supersyn FE SAE 0W-30	Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Excellent cold starting properties and low oil consumption.	ACEA A5/B5	–	–
TITAN SYN MC SAE 10W-40	Super High Performance, fuel-economy engine oil based on MC-synthesis for a variety of gasoline and diesel engines in passenger cars. Lower oil consumption.	ACEA A3/B4 API SN	MB- APPROVAL 229.3 PSA B71 2300	API CF MB 229.1
Gear Oils				
TITAN SINTOFLUID SAE 75W-80	Premium Performance Manual Transmission Fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-5	–	–
TITAN SINTOPOID SAE 75W-90	Premium Performance Axle Gear Oil for passenger cars, also for high-offset hypoid drives offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-5	–	–
TITAN SINTOPOID LS SAE 75W-90	Premium Performance, fully-synthetic multifunctional gear oil, formulated with fully-synthetic base oils. Suitable for axles and transfer gear-boxes with or without self-locking differentials and also as trouble shooter for conventional manual transmissions.	API GL-4/-5/-5 incl. LS	–	–

Product name	Description	Specifications	Approvals	FUCHS Recommendations
Automatic Transmission Fluids (ATF)				
TITAN ATF 6400	Premium Performance ATF with reduced viscosity specifically formulated for automatic transmissions of Japanese and American manufacturers. Licensed according to DEXRON VI and MERCON LV. Product dyeing: red.	JASO M315 TYPE 1A-LV	DEXRON VI	AISIN WARNER/ AW-1 JWS 3324
TITAN ATF 4400	Ultra High Performance ATF specifically formulated for Japanese passenger cars and light commercial vehicles, as well as for several European and American manufacturers. The high torque capacity exceeds the performance of many original fluids. Product dyeing: red.	JASO M315 TYPE 1A	–	DEXRON III JWS 3309/TYPE T-IV MITSUBISHI SP-II/-III
TITAN ATF 4000	Ultra High Performance ATF for use in automatic transmissions as well as other ATF applications. Licensed according to DEXRON III (H). Improved low-temperature shifting compared to DEXRON II. Product dyeing: red.	–	DEXRON III (H)	–
Continuously Variable Transmission Fluids (CVTF)				
TITAN CVTF FLEX	Ultra High Performance ATF specially designed for use in many CVT-gearboxes using push-belts or transmission chains made of steel. Product dyeing: none.	–	–	MITSUBISHI CVTF-J1/J4
Antifreeze				
MAINTAIN FRICOFIN	Super High Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine and phosphate. Product dyeing: blue-green.	ASTM D 3306 TYPE I ASTM D 4985 BS 6580:2010 SAE J814 SAE J1034	–	–
MAINTAIN FRICOFIN LL	Premium Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine, phosphate and silicates. Product dyeing: orange.	ASTM D 3306 TYPE I ASTM D 6210 TYPE I-FF BS 6580:2010 SAE J814	–	ASTM D 4985 SAE J1034 PSA B 71 5110
Brake Fluids				
MAINTAIN DOT 4 LV	Premium Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 3/4 ISO 4925 CLASS 3/4/6 SAE J 1703/1704	–	PSA S71 2114
MAINTAIN DOT 5.1	Ultra High Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 3/4/5.1 ISO 4925 CLASS 3/4/5-1 SAE J1703/J1704	–	–
MAINTAIN DOT 4 HT	Ultra High Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 3/4/5.1 ISO 4925 CLASS 3/4/5-1 SAE J1703/J1704	–	–

The information contained in this product information is based on the experience and know-how of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid.

Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH.
© FUCHS SCHMIERSTOFFE GMBH. All Rights reserved. Issue 03/2021

FUCHS SCHMIERSTOFFE GMBH
Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany
Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719
E-Mail: export-fs@fuchs.com • www.fuchs.com/de/en

PARTNER
des deutschen Kraftfahrzeuggewerbes

