

## Anti Freeze – New assortment

| Product                                       | Specifications  | Approvals   | FUCHS Recommendations  |
|---|---|---|--|
| MAINTAIN FRICOFIN S<br><i>Light green</i>     | ASTM D 3306 TYPE I<br>BS 6580:2010  | -   | -  |
| MAINTAIN FRICOFIN S -35<br><i>Light green</i> | ASTM D 3306 TYPE III<br>BS 6580:2010  | -   | -  |
| MAINTAIN FRICOFIN<br><i>Blue-green</i>        | AFNOR NF R 15-601 TYPE 1<br>AS/NZS 2108:2004 TYPE A<br>ASTM D 3306 TYPE I<br>ASTM D 4985<br>BS 6580:2010<br>CUNA NC 956-16<br>SAE J814<br>SAE J1034 | BMW GS 94000<br>(BMW N 600 69.0)<br>CAT / MWM TR 0199-99-2091<br>DEUTZ DQC CA-14<br>GE JENBACHER TA 1000-0201<br>MAN 324 TYPE NF<br>MAN 324 TYPE NF PRITARDER<br>MB-APPROVAL 325.0<br>MTU MTL 5048<br>PN-C 40007:2000<br>VOITH TURBO 172.00225010 | DAF 74001<br>LIEBHERR TLV 035/TLV 23009 A<br>OPEL/GM B 040 0240<br>VW TL 774-C (G11) |
| MAINTAIN FRICOFIN N<br><i>Blue</i>            | ASTM D4985<br>BS 6580<br>JIS K2234<br>KSM 2142<br>SAE J1034   | -   | Jl Case JIC-501<br>MAN 324 Typ NF<br>MTU MTL 5048<br>VW TL-774 C (G11)               |
| MAINTAIN FRICOFIN DP<br><i>Purple</i>         | AFNOR NF R 15-601 TYPE 1<br>AS/NZS 2108:2004 TYPE A<br>ASTM D 3306 TYPE I<br>ASTM D 4985<br>BS 6580:2010<br>SAE J814<br>CUMMINS CES 14603           | DEUTZ DQC CC-14<br>MAN 324 TYPE Si-OAT<br>MB-APPROVAL 325.5<br>MB-APPROVAL 325.6  | DETROIT DIESEL 93K217<br>SCANIA TB 1451<br>VW TL 774-G (G12++)                       |

| Product                                  | Specifications  | Approvals    | FUCHS Recommendations   |
|--|---|--------------|---|
| MAINTAIN FRICOFIN HDD<br><i>Yellow</i>   | ASTM D 3306 TYPE I<br>ASTM D 4985<br>ASTM D 6210 TYPE I-FF<br>ASTM D 7583<br>AS/NZS 2108:2004 TYPE A<br>BS 6580:2010<br>SAE J814<br>CHRYSLER MS 7170<br>CHRYSLER MS 9769<br>DETROIT DIESEL 7SE298<br>FORD ESE-M97B44-A<br>FORD ESE-M97B18-C<br>FORD WSS M97B51-A1<br>GM 1825M & GM 1899M<br>JIS K2234 | MTU MTL 5048 | CASE MS 1710<br>CAT EC-1<br>CUMMINS CES 14603<br>DETROIT DIESEL 93K217 (NOAT)<br>FREIGHTLINER 48-2288D<br>IVECO 18-1830<br>KENWORTH RO26-170-97<br>MAN 324 TYPE N<br>NEW HOLLAND WSN-M97B18-D<br>PACCAR CS 0185<br>TOYOTA Motor Corp. RP 329  |
| MAINTAIN FRICOFIN LL-YF<br><i>Yellow</i> | ASTM D 3306 TYPE I<br>ASTM D 6210 TYPE I-FF<br>BS 6580:2010<br>FORD WSS-M97-B44-D<br>JAGUAR LAND ROVER STJLR.651.5003   | CNH MAT 3624 | AFNOR NFR 15-601 TYPE I<br>AS/NZS 2108:2004 TYPE A<br>ASTM D 4985<br>SAE J1034<br>CHRYSLER MS 12106<br>CUMMINS (ISBe engines at DAF und Leyland)<br>DAF 74002 (different colour)<br>DETROIT DIESEL 93K217<br>DEUTZ DQC CB-14<br>FIAT 9.55523<br>GM 6277M<br>HYUNDAI MS 591-08<br>JASO M325<br>JIS K2234<br>KOMATSU AF-NAC (ready mix)<br>LIEBHERR MD 1-36-130<br>MAN 324 TYPE SNF<br>CAT / MWM TR 0199-99-2091<br>PSA B 71 5110<br>RENAULT TYPE D<br>TOYOTA TSK 2601G-8A<br>VW TL 774-D/F (G12+ / different colour)<br>VOLVO COOLANT VCS (STD 418-0001) |

| Product                                       | Specifications  | Approvals  | FUCHS Recommendations  |
|---|---|--|--|
| MAINTAIN FRICOFIN LL PG<br><i>Light green</i> | ASTM D3306<br>BS 6580<br>KS M 2142<br>Önorm V5123<br>SAE J1034<br>UNE 26-361-88/1   | -  | -  |
| MAINTAIN FRICOFIN LL<br><i>Orange</i>         | ASTM D 3306 TYPE I<br>ASTM D 6210 TYPE I-FF<br>BS 6580:2010<br>SAE J814<br>FORD WSS-M97-B44-D<br>JAGUAR LAND ROVER STJLR.651.5003<br>FVV Heft R443<br>KSM 2142<br>UNE 26-361-88/1 | Bez.Reg.Arnsg. E62.12.22.64-2011-1<br>CAT / MWM TR 0199-99-2091<br>DAF 74002<br>DEUTZ DQC CB-14<br>MAN 324 TYPE SNF<br>MB-APPROVAL 325.3 | AFNOR NFR 15-601 TYPE I<br>AS/NZS 2108:2004 TYPE A<br>ASTM D 4985<br>SAE J1034<br>ADE (ATLANTIS DIESEL ENGINES)<br>BAIC GROUP FOTON Q-FPT 2313005-2013<br>CATERPILLAR MAK A4.05.09.01<br>CHRYSLER MS 12106<br>CNH MAT 3624<br>CUMMINS (ISBe engines at DAF and Leyland)<br>CUMMINS CES 14603, CES 14439<br>DETROIT DIESEL 93K217<br>FIAT 9.55523<br>GM GMW 3420 (6277M)<br>HYUNDAI MS 591-08<br>JASO M325<br>JIS K2234<br>JOHN DEERE JDM H5<br>KOMATSU AF-NAC (ready mix) (07.892 (2009))<br>LIEBHERR MD 1-36-130<br>MACK 014 GS 17009<br>MAZDA MEZ MN 121 D<br>PSA B 71 5110<br>RENAULT 41-01-001/- -S Type D<br>SAAB B 040 1065<br>SKODA 61-0-0257<br>TOYOTA TSK 2601G-8A<br>VAUXHALL GME L1301<br>VW TL 774-D/F (G12+ / different colour)<br>VOLVO COOLANT VCS (STD 418-0001) |

| New Product                               | Specifications  | Approvals | FUCHS Recommendations  |
|---|---|-----------|--|
| MAINTAIN FRICOFIN LL -35<br><i>Orange</i> | ASTM D 3306 TYPE III<br>ASTM D 6210 TYPE III-FF<br>BS 6580:2010 | -         | ASTM D 4985<br>SAE J1034<br>CATERPILLAR MAK A4.05.09.01<br>CAT / MWM TR 0199-99-2091<br>CHRYSLER MS 12106<br>CNH MAT 3624<br>CUMMINS CES 14603, CES 14439<br>DAF 74002<br>DETROIT DIESEL 93K217<br>DEUTZ DQC CB-14<br>FIAT 9.55523<br>FORD WSS-M97-B44-D<br>GM GMW 3420 (6277M)<br>HYUNDAI MS 591-08<br>JAGUAR LAND ROVER STJLR.651.5003<br>JOHN DEERE JDM H5<br>KOMATSU AF-NAC (ready mix) (07.892 (2009))<br>LIEBHERR MD 1-36-130<br>MACK 014 GS 17009<br>MAN 324 TYPE SNF<br>MAZDA MEZ MN 121 D<br>PSA B 71 5110<br>RENAULT 41-01-001/- -S Type D<br>SAAB B 040 1065<br>SKODA 61-0-0257<br>TOYOTA TSK 2601G-8A<br>VAUXHALL GME L1301<br>VOLVO COOLANT VCS (STD 418-0001)<br>VW TL 774-D/F (G12+ / different colour) |

Fuchs Oil Finland Oy

Wolffintie 36 M10/I  
65200 Vaasa

Puh 020-7459 660  
Fax 020-7459 667

fuchs@fuchs.fi  
fuchs.com/fi