



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for Ford.

Product name	Description	Specifications	Approvals	FUCHS Recommendations
Engine Oils				
TITAN GT1 FLEX 952 SAE 0W-20 	Premium Performance Engine Oil specially designed for modern FORD vehicles, for extreme fuel-economy characteristics and reduced CO ₂ emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves. Additionally applicable in hybrid vehicles of different manufacturers.	ACEA C6, C5 API SN PLUS API SP FORD WSS- M2C952-A1	–	FORD WSS- M2C947-A FORD WSS- M2C947-B1 FORD WSS- M2C962-A1 ILSAC GF-5
TITAN GT1 FLEX 5 SAE 0W-20 	Premium Performance Engine Oil. Specially designed for highly stressed downsized engines with maximum power output, for extreme fuel-economy characteristics and reduced CO ₂ emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves. With BluEV Technology additionally applicable in hybrid vehicles of different manufacturers.	ACEA C6,C5 FORD WSS- M2954-A1	–	FORD WSS- M2C947-A FORD WSS- M2C947-B1 FORD WSS- M2C962-A1 ILSAC GF-5
TITAN SUPERSYN F ECO-FE SAE 0W-30	Ultra High Performance, extreme fuel-economy engine oil especially developed for modern Ford Diesel engines. Excellent cold starting and lower oil consumption.	ACEA C2 FORD WSS- M2C950-A	–	–
TITAN SUPERSYN F ECO-B SAE 5W-20	Ultra High Performance, extreme fuel-economy engine oil especially developed for Ford EcoBoost gasoline engines. Optimum cold starting and lower oil consumption.	ACEA C5 API SN FORD WSS- M2C948-B	–	ACEA A1/B1 CHRYSLER MS 6395 FORD WSS- M2C925-A FORD WSS- M2C925-B FORD WSS- M2C945-A ILSAC GF-5
TITAN SUPERSYN F ECO-DT SAE 5W-30	Ultra High Performance, extreme fuel-economy engine oil especially suitable for Ford DuraTorq-Diesel engines. Optimum cold starting and lower oil consumption.	ACEA A5/B5 API SL FORD WSS- M2C913-D	JAGUAR LAND ROVER STJLR.03.5003	ACEA A1/B1 API CF FORD WSS- M2C913-A FORD WSS- M2C913-B FORD WSS- M2C913-C
Gear Oils				
TITAN SINTOFLUID SAE 75W-80	Premium Performance Manual Transmission Fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-4	–	FORD WSS- M2C200 C3
TITAN SINTOPOID LS SAE 75W-90	Premium Performance, fully-synthetic multifunctional gear oil, formulated with fully-synthetic base oils. Suitable for axles and transfer gear-boxes with or without self-locking differentials and also as trouble shooter for conventional manual transmissions.	API GL-4/-5/-5 inkl. LS	–	FORD WSS- M2C200-C/C2
TITAN SINTOPOID LS SAE 75W-140	Premium Performance Gear Oil for axle and transfer gearboxes, formulated with fully-synthetic base oils. Suitable for axle and transfer gearboxes with and without limited slip differential.	API GL-5	–	FORD WSL- M2C192-A
Double Clutch Transmission Fluids (DCTF)				
TITAN FFL-4	Premium Performance DCTF. Specially developed for GETRAG/BMW Double Clutch Transmission with wet clutch.	–	GETRAG (PWA05043)	FORD WSS- M2C936-A

Product name	Description	Specifications	Approvals	FUCHS Recommendations
TITAN FFL-7 A BluEV TECHNOLOGY	Premium Performance DCTF. Specially developed for the third generation wet clutch DCT of Magna GETRAG.	–	–	FORD WSS- M2C218-A1 (F-DC)
Automatic Transmission Fluids (ATF)				
TITAN ATF 6400 BluEV TECHNOLOGY	Premium Performance ATF with reduced viscosity specifically formulated for automatic transmissions of Japanese and American manufacturers. Licensed according to DEXRON VI and MERCON LV. Additionally also suitable for use in hybrid applications from various manufacturers. Product dyeing: red.	JASO M315 TYPE 1A-LV	DEXRON VI	FORD MERCON LV
TITAN ATF 4400 Advanced Circular Technologies	Ultra High Performance ATF specifically formulated for Japanese passenger cars and light commercial vehicles, as well as for several European and American manufacturers. The high torque capacity exceeds the performance of many original fluids. Product dyeing: red.	JASO M315 TYPE 1A	–	DEXRON III FORD MERCON FORD MERCON V FORD M2C924- A/M2C922-A1 FORD WSS- M2C919-E FORD WSS- M2C202-B
Continuously Variable Transmission Fluids (CVTF)				
TITAN CVTF PRO 236.20	Premium Performance CVTF specially designed for Mercedes-Benz and Ford CVT-gearboxes. Product dyeing: none.	–	FORD WSS- M2C928-A	–
TITAN CVTF FLEX Advanced Circular Technologies	Premium Performance CVTF specially designed for use in many CVT-gearboxes using push-belts or transmission chains made of steel. Product dyeing: none.	–	–	FORD WSS- M2C933-A/MERCON C
Central Hydraulic / Power Steering Fluids				
TITAN CHF 202 BluEV TECHNOLOGY	Premium Performance Power Steering and Central Hydraulic Fluid with a wide application and approval profile for various manufacturers. Product dyeing: green.	FORD WSS- M2C204-A2	–	–
Antifreeze				
FRICOFIN PS BluEV TECHNOLOGY	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites and borates with PSi-OAT-technology. With BluEV Technology additionally applicable in hybrid and electrical vehicles of different manufacturers. Product dyeing: green.	AFNOR NF-R- 15-601 TYPE I ASTM D3306-20 TYPE I ASTM D4985 BS 6580.2010 FVV Heft R530:2005 JIS K2234:2018 UNE 26-361- 88/1	–	FORD ESD- M97B49-A
FRICOFIN LD	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites, phosphates and silicates with X-OAT-technology. Product dyeing: orange.	ASTM D3306 TYPE I ASTM D6210 TYPE I-FF GB 27943.1- 2022 Tata Motors – Jaguar (STJLR.03.5212) VOLVO VCS-2	–	FORD WSS M97B44-D

Product name	Description	Specifications	Approvals	FUCHS Recommendations
Brake Fluids				
TITAN DOT 514 LV 	Premium Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 3/4/5.1 ISO 4925 CLASS 3/4/5- 1/6/7 JIS K2233 CLASS 3/4/5/6 SAE J 1703/1704	–	FORD M6C65-A2

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH. © FUCHS LUBRICANTS GERMANY GmbH. All Rights reserved. Issue 08/2024

FUCHS LUBRICANTS GERMANY GmbH
Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany
Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719
E-Mail: export-flg@fuchs.com • www.fuchs.com/de/en

PARTNER 
des deutschen Kraftfahrzeuggewerbes