

# LUBRICANTS FOR MITSUBISHI PASSENGER CARS



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for Mitsubishi.

Product name	Description	Specifications	Approvals	FUCHS Recommendations
<b>Engine Oils</b>				
<b>TITAN GT1 FLEX 5 SAE 0W-20</b>  	Premium Performance Engine Oil. Specially designed for highly stressed downsized engines with maximum power output, for extreme fuel-economy characteristics and reduced CO <sub>2</sub> emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves. Additionally applicable in hybrid vehicles of different manufacturers such as Toyota or Mercedes-Benz.	ACEA C6, C5 API SN PLUS RC API SP RC ILSAC GF-6A	–	ILSAC GF-5
<b>TITAN GT1 FLEX C3 SAE 0W-30</b>  	Premium Performance engine oil for modern cars and vans. Especially developed for BMW, VW, Porsche und Mercedes-Benz vehicles with exhaust gas aftertreatment and turbochargers. Excellent Cold-Start properties, low oil consumption and reduced emissions. Additionally applicable in hybrid vehicles of different manufacturers.	ACEA C3	VW 504 00/507 00	API SN
<b>TITAN GT1 FLEX C23 SAE 5W-30</b>  	Premium Performance, extreme fuel-economy engine oil with optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals. Additionally applicable in hybrid vehicles of different manufacturers.	ACEA C3, C2 API SP	–	–
<b>TITAN SUPERSYN LONGLIFE SAE 5W-40</b>	Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption.	ACEA A3/B4 API SN/SM	PSA B71 2296	API CF
<b>TITAN SYN MC SAE 10W-40</b>	Ultra High Performance, fuel-economy engine oil based on MC-synthesis for a variety of gasoline and diesel engines in passenger cars. Lower oil consumption.	ACEA A3/B4 API SN	MB-FREIGABE 229.3	API CF MB 229.1 PSA B71 2300
<b>Gear Oils</b>				
<b>TITAN SINTOFLUID SAE 75W-80</b>	Premium Performance Manual Transmission Fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-4	–	–
<b>TITAN SINTOPOID LS SAE 75W-90</b>	Premium Performance, fully-synthetic multifunctional gear oil, formulated with fully-synthetic base oils. Suitable for axles and transfer gear-boxes with or without self-locking differentials and also as trouble shooter for conventional manual transmissions.	API GL-4/-5/-5 inkl. LS	–	–
<b>Automatic Transmission Fluids (ATF)</b>				
<b>TITAN ATF 8400 ULV</b>	Premium Performance ATF with extremely reduced viscosity specifically formulated for automatic transmissions of Japanese manufacturers. Product dyeing: red.	–	–	AISIN WARNER AW- 2 DEXRON ULV PSA 16 350 560 80
<b>TITAN ATF 6400</b>  	Premium Performance ATF with reduced viscosity specifically formulated for automatic transmissions of Japanese and American manufacturers. Licensed according to DEXRON VI and MERCON LV. Additionally also suitable for use in hybrid applications from various manufacturers. Product dyeing: red.	JASO M315 TYPE 1A-LV	DEXRON VI	AISIN WARNER/ AW-1 JWS 3324 MITSUBISHI ATF-J3 MITSUBISHI ATF-PA MITSUBISHI MA1

# LUBRICANTS FOR MITSUBISHI PASSENGER CARS



Product name	Description	Specifications	Approvals	FUCHS Recommendations
<b>TITAN ATF 4400</b>	Ultra High Performance ATF specifically formulated for Japanese passenger cars and light commercial vehicles, as well as for several European and American manufacturers. The high torque capacity exceeds the performance of many original fluids. Product dyeing: red.	JASO M315 TYPE 1A	–	DEXRON III JWS 3309/TYP T-IV MITSUBISHI SP-II/-III
<b>Continuously Variable Transmission Fluids (CVTF)</b>				
<b>TITAN CVTF FLEX</b>	Premium Performance CVTF specially designed for use in many CVT-gearboxes using push-belts or transmission chains made of steel. Product dyeing: none.	–	–	MITSUBISHI CVTF-J1/J4
<b>Antifreeze</b>				
<b>MAINTAIN FRICOFIN LL</b>	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites, amines, phosphates and silicates with OAT-technology. Product dyeing: orange.	ASTM D 3306 TYPE I ASTM D 6210 TYPE I-FF BS 6580:2010 SAE J814	–	ASTM D 4985 SAE J1034 PSA B 71 5110
<b>Brake Fluids</b>				
<b>MAINTAIN DOT 514 LV</b>	Premium Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 3/4/5.1 ISO 4925 CLASS 3/4/5- 1/6/7 JIS K2233 CLASS 3/4/5/6 SAE J 1703/1704	–	PSA S71 2114



The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH. © FUCHS LUBRICANTS GERMANY GmbH. All Rights reserved. Issue 12/2022

FUCHS LUBRICANTS GERMANY GmbH  
Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany  
Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719  
E-Mail: export-flg@fuchs.com • www.fuchs.com/de/en

