












Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. FUCHS offers also the right lubricants for Opel.

Product name	Description	Specifications	Approvals	FUCHS Recommendations
Engine Oils				
TITAN GT1 FLEX 5 SAE 0W-20 	Premium Performance Engine Oil. Specially designed for highly stressed downsized engines with maximum power output, for extreme fuel-economy characteristics and reduced CO ₂ emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves. Additionally applicable in hybrid vehicles of different manufacturers.	ACEA C6, C5 API SN PLUS RC API SP RC ILSAC GF-6A	OPEL OV0401547 – A20	ILSAC GF-5
TITAN GT1 PRO 2010 SAE 0W-20 Advanced Circular Technologies	Premium Performance Leichtlauf-Motorenöl der Spitzenklasse. Speziell entwickelt für moderne PSA-Fahrzeuge, für extreme Kraftstoff- und CO ₂ -Einsparung dank der nachhaltigen FUCHS Advanced Circular Technologie (ACT). Exzellente Kaltstarteigenschaften, schnelle Durchlaufzeiten und herausragende Leistungsreserven.	ACEA C5 API SP	PSA B71 2010	–
TITAN GT1 PRO 2312 SAE 0W-30	Premium Performance, fuel-economy engine oil for modern passenger cars and light commercial vehicles. Specially developed for latest PSA gasoline and diesel vehicles with exhaust after treatment and turbocharger. Excellent cold starting, lower oil consumption and minimized exhaust emissions.	ACEA C2	PSA B71 2312	–
TITAN GT1 PRO FPW03 SAE 5W-30 NEU	Premium Performance engine oil for passenger cars and light commercial vehicles, specially developed for Stellantis engines requiring the new specification FPW9.55535/03. Optimum cold starting, reduced oil consumption, and minimised exhaust emissions.	ACEA C3 API SN PLUS	–	STELLANTIS FPW9.55535/03 PSA B71 2290 PSA B71 2297
TITAN GT1 FLEX C23 SAE 5W-30 	Premium Performance, extreme fuel-economy engine oil with optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals. Additionally applicable in hybrid vehicles of different manufacturers.	ACEA C3, C2 API SN	OPEL OV0401547 – D30 OPEL OV0401547 – G30	GM-LL-A-025 GM-LL-B-025
Gear Oils				
TITAN SINTOFLUID FE SAE 75W 	Premium Performance Manual Transmission Fluid offering increased efficiency in passenger cars due to its low viscosity and can also be used in reducer gearboxes of hybrid vehicles. Reduces fuel consumption and offers best properties at low temperature. Suitable as fill for life fluid according to manufacturer.	API GL-4	–	PSA B71 2316
TITAN SINTOFLUID SAE 75W-80	Premium Performance Manual Transmission Fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-4	–	OPEL 19 40 182 OPEL 19 40 757 OPEL 19 40 768 OPEL 19 40 776
TITAN SINTOPOID LS SAE 75W-90	Premium Performance, fully-synthetic multifunctional gear oil, formulated with fully-synthetic base oils. Suitable for axles and transfer gear-boxes with or without self-locking differentials and also as trouble shooter for conventional manual transmissions.	API GL-4/-5/-5 inkl. LS	–	–

Product name	Description	Specifications	Approvals	FUCHS Recommendations
Automatic Transmission Fluids (ATF)				
TITAN ATF 6400 	Premium Performance ATF with reduced viscosity specifically formulated for automatic transmissions of Japanese and American manufacturers. Licensed according to DEXRON VI and MERCON LV. Additionally also suitable for use in hybrid applications from various manufacturers. Product dyeing: red.	JASO M315 TYPE 1A-LV	DEXRON VI	AISIN WARNER/ AW-1 GM 9256039/ 88863400
TITAN ATF 4400 	Ultra High Performance ATF specifically formulated for Japanese passenger cars and light commercial vehicles, as well as for several European and American manufacturers. The high torque capacity exceeds the performance of many original fluids. Product dyeing: red.	JASO M315 TYPE 1A	–	DEXRON III JWS 3309/ TYPE T-IV
TITAN ATF 4000	Ultra High Performance ATF for use in automatic transmissions as well as other ATF applications. Licensed according to DEXRON III (H). Improved low-temperature shifting compared to DEXRON II. Product dyeing: red.	–	DEXRON III (H)	OPEL 19 40 707 OPEL 19 40 767
Continuously Variable Transmission Fluids (CVTF)				
TITAN CVTF FLEX 	Premium Performance CVTF specially designed for use in many CVT-gearboxes using push-belts or transmission chains made of steel. Product dyeing: none.	–	–	GM 19260800 GM DEX-CVT GM HP CVTF
Central Hydraulic / Power Steering Fluids				
TITAN CHF 11S	Premium Performance TCF specially designed for use in many transfer cases with wet running clutch.	–	PSA S71 2710	OPEL B 040 0070
TITAN CHF 202 	Premium Performance Power Steering and Central Hydraulic Fluid with a wide application and approval profile for various manufacturers. Product dyeing: green.	–	OPEL B 040 2012	–
Antifreeze				
FRICOFIN LD	Premium Performance Coolant Concentrate based on monoethylene glycol. Free of nitrites, phosphates and silicates with X-OAT-technology. Product dyeing: orange.	ASTM D3306 TYPE I ASTM D6210 TYPE I-FF	–	GM 6277M GMW 3420
FRICOFIN PS 	Premium Performance Coolant Ready-Mix based on monoethylene glycol. Free of nitrites and borates with PSi-OAT-technology. Offers frost protection down to -40°C. With BluEV Technology additionally applicable in hybrid and electrical vehicles of different manufacturers. Product dyeing: green.	ASTM D3306-20 TYPE I ASTM D4985	–	GME L1301 (Opel, Vauxhall)

Product name	Description	Specifications	Approvals	FUCHS Recommendations
Brake Fluids				
TITAN DOT 514 LV 	Premium Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles	FMVSS NR. 116 DOT 3/4/5.1 ISO 4925 CLASS 3/4/5-1/6/7 JIS K2233 CLASS 3/4/5/6 SAE J 1703/1704	–	GM Europa GMW 3356 PSA S71 2114

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS GERMANY GmbH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft or spacecraft. Our products may be used in the manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS GERMANY GmbH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS GERMANY GmbH. © FUCHS LUBRICANTS GERMANY GmbH. All Rights reserved. Issue 08/2024

FUCHS LUBRICANTS GERMANY GmbH
Export Division • Friesenheimer Straße 19 • 68169 Mannheim/Germany
Phone: +49 621 3701-1703 • Fax: +49 621 3701-7719
E-Mail: export-flg@fuchs.com • www.fuchs.com/de/en

PARTNER
des deutschen Kraftfahrzeuggewerbes

