

Alert Turbine Test

Within the scope of our service Lab Advisor Alert, we offer a complete analysis package for turbine oils. Alert Turbine Test is part of a systematic maintenance allowing you to quickly get an indication if something is not right in your system. It is easy to get started with Alert Turbine Test. Order a sampling kit where you order your other lubricant products.

It is easy to get started with Alert Turbine Test. Order a sampling kit where you order your other lubricant products. The first time you use Alert you register the system you wish to send samples from and then you can easily print labels via our website. After about a week, you receive the analysis report via e-mail and in addition you have access to all previous reports on our website.

Order

- Item number 940057225
- For questions please contact your sales representative

Below you will find an overview of the analyzes included in Alert Turbine Test.

Test	Method	Turbine B
Air Release @ 50°C	ASTM D3427	X
Appearance	In-house	X
Water Separation @ 54°C	ASTM D1401	X
Ferrous Debris by PQ Particle Quantifier	In-house	X
Foaming Characteristics @ 24° C (Seq I)	IP 146	X
ISO Particle Counting	ISO 4406	X
Kinematic Viscosity @ 40 and 100°C	ASTM D7279	X
Rotating Pressure Vessel Oxidation Test (RPVOT)	ASTM D2272	X
RULER	ASTM D6971	X
Neutralization number	IP 139/ASTM D974	X
Varnish Potential by MPC	ASTM D7843	X
Water Content by Karl Fischer	ASTM D6304	X
Wear Metals And Contamination Elements by ICP	ASTM D5185	X