

## SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: RENOLIN ROCKDRILL 46 U

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Lubricant

**Uses advised against:**No uses advised against identified.

1.3 Details of the supplier of the safety data sheet

Manufacturer / Supplier FUCHS LUBRICANTS NORWAY AS

Fredrik Selmersvei 6

0663 Oslo Norway

Telephone: +47 21 99 59 50

Contact Person: HSE Advisor

E-mail: fse-hseasc@fuchs.com Telephone: +46 8 128 25 000

**1.4 Emergency telephone number:** +47 22 59 13 00

**SECTION 2: Hazards identification** 

2.1 Classification of the substance or mixture

The product has been classified and labelled as hazardous according to regulation (EU) 1272/2008 (CLP).

Classification according to Regulation (EC) No 1272/2008 as amended.

**Environmental Hazards** 

Chronic hazards to the aquatic environment

Category 3

H412: Harmful to aquatic life with long lasting

1/11

effects.

**Hazard summary** 

Physical Hazards: No data available.

2.2 Label Elements

**Hazard Statement(s):** H412: Harmful to aquatic life with long lasting effects.

**Precautionary Statements** 

**Prevention:** P273: Avoid release to the environment.

**Disposal:** P501: Dispose of contents/ container to an approved facility in accord-

ance with local, regional, national and international regulations.

Revision Date: 09.09.2024 Version: 1.4

Print date: 10.09.2024



Product name: RENOLIN ROCKDRILL 46 U

### Supplemental label information

EUH208: Contains: Alkyl methacrylate, Alkyl amine. May produce an allergic

reaction.

2.3 Information on other haz-

ards

By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective

equipment (item 8) are kept. The product may not be released into the envi-

ronment without control.

**Endocrine disrupting prop-**

erties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation

(EU) 2018/605 at levels of 0.1% or higher.

Results of PBT and vPvB

assessment:

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very

bioaccumulative (vPvB) at levels of 0.1% or higher.

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

**General information:** Mixture containing severely refined base oils and additives.

Chemical name	Identifier		REACH Registra- tion No.	Notes
Base oil, naphthenic	EINECS: 265-156-6	50,00% - <100,00%	01-2119480375-34	
Base oil, low viscous	EINECS: 265-158-7	1,00% - <10,00%	01-2119487077-29	
Alkyl methacrylate	EINECS: 201-297-1	0,10% - <1,00%	01-2119452498-28	
Alkyl amine	EINECS: 701-175-2	0,10% - <0,25%	01-2119456798-18	
alkenyl amine, long-chain	EC: 627-034-4	0,01% - <0,25%	01-2119473797-19	

<sup>\*</sup> All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### Classification

Chemical name	Identifier	Classificati	Classification	
Base oil, naphthenic	EINECS: 265-156-6	CLP: Asp.	Tox. 1;H304	
Base oil, low viscous	EINECS: 265-158-7	CLP: Asp.	Tox. 1;H304	
Alkyl methacrylate	EINECS: 201-297-1		n. Liq. 2;H225, Skin Irrit. 2;H315, Skin Sens. H317, STOT SE 3;H335	
Alkyl amine	EINECS: 701-175-2	Acut	Corr. 1B;H314, Skin Sens. 1A;H317, Aquatic te 1;H400, Aquatic Chronic 1;H410, Acute Tox. 3;H311, Acute Tox. 2;H330	
alkenyl amine, long-chain	EC: 627-034-4	3;H3 Aqua Dam	te Tox. 4;H302, Asp. Tox. 1;H304, STOT SE 335, STOT RE 2;H373, Skin Corr. 1B;H314, atic Acute 1;H400, Aquatic Chronic 1;H410, Eye n. 1;H318; M-Factor (aquatic acute): 10; M-or (aquatic chronic): 10	

CLP: Regulation No. 1272/2008.

Revision Date: 09.09.2024 Version: 1.4

Print date: 10.09.2024 SDS\_NO - EN - 000000000602001207

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.



Product name: RENOLIN ROCKDRILL 46 U

#### specific concentration limit

Chemical name		specific concentra- tion limit		Category	Hazard state- ments
Alkyl amine	EINECS: 701-175-2	>= 5 %	Skin sensitizer	1A	H317

For the wording of the listed hazard statements refer to section 16.

Please note that the mineral oils and petroleum distillates used in our products are severely refined and have a DMSO extract < 3% as measured by method IP 346 and are not classified as carcinogenic according to Nota L/ Nota N of Annex VI of Regulation EC 1272/2008."

### **SECTION 4: First aid measures**

General: Instantly remove any clothing soiled by the product.

4.1 Description of first aid measures

Inhalation: Supply fresh air; consult doctor in case of symptoms.

**Eve contact:** Promptly wash eyes with plenty of water while lifting the eye lids.

**Skin Contact:** Wash with soap and water.

Ingestion: Rinse mouth thoroughly.

4.2 Most important symptoms and effects, both acute and delayed:

May cause skin and eye irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Get medical attention if symptoms occur.

### **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing me-

dia:

CO2, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant add-

Unsuitable extinguishing media:

ture:

Water with a full water jet.

5.2 Special hazards arising from the substance or mix-

During fire, gases hazardous to health may be formed.

5.3 Advice for firefighters

Special fire-fighting proce-

dures:

Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water inaccordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

Revision Date: 09.09.2024 Version: 1.4

Print date: 10.09.2024



Product name: RENOLIN ROCKDRILL 46 U

Special protective equipment for fire-fighters:

Self-contained breathing apparatus and full protective clothing must be

worn in case of fire.

### SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

In case of spills, beware of slippery floors and surfaces.

**6.2 Environmental Precautions:** 

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Prevent from spreading (e.g. by binding or oil barriers). Environmental manager must be informed of all major spillages. Do not allow to

enter drainage system, surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acidbinders, universal binders, sawdust). Dispose of the material collected according to regula-

tions. Stop the flow of material, if this is without risk.

6.4 Reference to other sections:

See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on dis-

posal.

### **SECTION 7: Handling and storage:**

7.1 Precautions for safe han-

dling:

Prevent formation of aerosols. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Observe good industrial hygiene practices. Pro-

vide adequate ventilation.

7.2 Conditions for safe storage, including any incompatibili-

ties:

Local regulations concerning handling and storage of waterpolluting products have to be followed. Do not heat up to temperatures close to the flash

point.

7.3 Specific end use(s): Not applicable

## **SECTION 8: Exposure controls/personal protection**

#### 8.1 Control Parameters

**Occupational Exposure Limits** 

Chemical name	Туре	Exposure Lim	it Values	Source
Base oil, naphthenic - Mist.	NORMEN		1 mg/m3	Norway. Regulation No. 1358 on Measures and Limit Values for Physical and Chemical Factors in Work Environment and Infection Groups for Biological Factors, as amended (12 2011)
Alkyl methacrylate	NORMEN	25 ppm	100 mg/m3	Norway. Regulation No. 1358 on Measures and Limit Values for Physical and Chemical Factors in Work Environment and Infection Groups for Biological Factors, as amended (12 2011)
Alkyl methacrylate	STEL	100 ppm	400 mg/m3	Norway. Regulation No. 1358 on Measures and Limit Values for Physical and Chemical Factors in Work Environment and Infection Groups for Biological Factors, as amended (01 2013)

Revision Date: 09.09.2024 Print date: 10.09.2024



Product name: RENOLIN ROCKDRILL 46 U

8.2 Exposure controls

Appropriate engineering

controls:

Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

**General information:** Wash hands before breaks and after work. Use personal protective equip-

ment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be ad-

hered to inhandling the chemicals or the mineral oil products.

**Eye/face protection:** Safety glasses (EN 166) recommended during refilling. Avoid contact with

skin and eyes. Goggles/face shield are recommended. If risk of splashing,

wear safety goggles or face shield.

Skin protection

**Hand Protection:** Material: Nitrile butyl rubber (NBR).

Min. Breakthrough time: >= 480 min

Recommended thickness of the material: >= 0,38 mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufactur-

er of the protective gloves and has to be observed.

Other: Do not carry cleaning cloths impregnated with the product in trouser pock-

ets. Wear suitable protective clothing.

**Respiratory Protection:** Ensure good ventilation/exhaustion at the workplace. Avoid breathing va-

pour/ aerosol.

Thermal hazards: Not known.

**Hygiene measures:** Always observe good personal hygiene measures, such as washing after

handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated foot-

wear that cannot be cleaned.

**Environmental Controls:** No data available.

### **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

**Appearance** 

Physical state:liquidForm:liquidColor:Yellow

Revision Date: 09.09.2024 Version: 1.4

Print date: 10.09.2024 SDS\_NO - EN - 000000000602001207



Product name: RENOLIN ROCKDRILL 46 U

Odor: Characteristic

pH: substance/mixture is non-soluble (in water)

Freezing point:  $-57 \,^{\circ}\text{C}$ Boiling Point:  $> 152 \,^{\circ}\text{C}$ 

Flash Point: 152 °C (DIN EN ISO 2592)

Flammability (solid, gas): not determined

Explosion Limit - Upper (%):Not applicable for mixturesExplosion Limit - Lower (%):Not applicable for mixturesVapor pressure:Not applicable for mixturesRelative vapor density:Not applicable for mixtures

**Density:** 0,90 g/cm3 (15 °C) (DIN 51757)

Solubility(ies)

Solubility in Water: Insoluble in water Solubility (other): No data available.

Partition coefficient (n-octanol/water): Not applicable for mixtures

Auto-ignition temperature: > 250 °C

**Decomposition Temperature:** not determined

Kinematic viscosity: 46 mm2/s (40 °C, DIN EN ISO 3104)

Particle characteristics:Not applicable9.2 Other informationNo data available.

## **SECTION 10: Stability and reactivity**

**10.1 Reactivity:** Stable under normal use conditions.

**10.2 Chemical Stability:** Stable under normal use conditions.

10.3 Possibility of hazardous

reactions:

Stable under normal use conditions.

**10.4 Conditions to avoid:** Stable under normal use conditions.

**10.5 Incompatible Materials:** Strong oxidizing substances. Strong acids. Strong bases.

**10.6 Hazardous Decomposition** Thermal decomposition or combustion may liberate carbon oxides and oth-

**Products:** er toxic gases or vapors.

### **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity** 

Oral

**Product:** Not classified for acute toxicity based on available data.

Revision Date: 09.09.2024 Version: 1.4

Print date: 10.09.2024



Product name: RENOLIN ROCKDRILL 46 U

Specified substance(s)

Base oil, low viscous LD 50 (Rat): > 5.000 mg/kg

Alkyl amine LD 50 (Rat): 612 mg/kg (OECD 401)

alkenyl amine, long-chain LD 50 (Rat): 1.689 mg/kg (OECD 401)

**Dermal** 

**Product:** ATEmix: 221.731 mg/kg

Specified substance(s)

Base oil, low viscous LD 50 (Rabbit): > 5.000 mg/kg (OECD 402)

Alkyl amine LD 50 (Rat): 251 mg/kg (OECD 402)

Inhalation

**Product:** ATEmix: 1.051,24 mg/l Vapour

Specified substance(s)

Base oil, naphthenic LC 50 (Rat, 4 h): > 5,53 mg/l Dust and mist

Base oil, low viscous LC 50 (Rat, 4 h): > 5,1 mg/l Dust and mist

Alkyl amine LC 50 (Rat, 4 h): 1,19 mg/l (OECD 403) Vapour

Skin Corrosion/Irritation:

**Product:** Based on available data, the classification criteria are not met.

Specified substance(s)

Base oil, low viscous (Rabbit):
Not irritant.

**Serious Eye Damage/Eye Irritation:** 

**Product:** Based on available data, the classification criteria are not met.

Specified substance(s)

Base oil, low viscous OECD 405 (Rabbit):

Not irritant.

**Respiratory or Skin Sensitization:** 

**Product:** Skin sensitizer: Based on available data, the classification criteria are not

met.

Respiratory sensitizer: Based on available data, the classification criteria

7/11

are not met.

Specified substance(s)

Base oil, low viscous

No sensitizing effect (guinea pig); OECD 406

**Germ Cell Mutagenicity** 

**Product:** Based on available data, the classification criteria are not met.

Carcinogenicity

**Product:** Based on available data, the classification criteria are not met.

Reproductive toxicity

Revision Date: 09.09.2024 Version: 1.4

Print date: 10.09.2024



8/11

Product name: RENOLIN ROCKDRILL 46 U

**Product:** Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Single Exposure** 

**Product:** Based on available data, the classification criteria are not met.

**Specific Target Organ Toxicity - Repeated Exposure** 

**Product:** Based on available data, the classification criteria are not met.

**Aspiration Hazard** 

**Product:** Based on available data, the classification criteria are not met.

11.2 Information on other haz-

ards

**Endocrine disrupting properties** 

**Product:** The substance/mixture does not contain components considered to have

endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation

(EU) 2018/605 at levels of 0.1% or higher.

SECTION 12: Ecological information

**Acute toxicity** 

**Product:** Based on available data, the classification criteria are not met.

**Fish** 

Specified substance(s)

Base oil, naphthenic LC 50 (Fish, 96 h): > 101 mg/l

Base oil, low viscous LL 50 (Fish, 96 h): > 100 mg/l

alkenyl amine, long-chain LC 50 (Fish, 96 h): 0,06 mg/l

Aquatic Invertebrates Specified substance(s)

Base oil, low viscous EC 50 (Water Flea, 48 h): > 1.000 mg/l

alkenyl amine, long-chain EC 50 (Water Flea, 48 h): 0,011 mg/l

Chronic ToxicityProduct: Based on available data, the classification criteria are met.

Aquatic Invertebrates Specified substance(s)

Base oil, low viscous NOEC (Water Flea, 21 d): 10 mg/l

alkenyl amine, long-chain NOEC (Water Flea, 21 d): 0,013 mg/l

Toxicity to Aquatic Plants Specified substance(s)

Base oil, low viscous NOEC (Alga, 72 h): > 100 mg/l

alkenyl amine, long-chain EC 50 (Alga, 72 h): 0,12 mg/l

EC 10 (Alga, 72 h): 0,029 mg/l

12.2 Persistence and Degradability

Revision Date: 09.09.2024 Version: 1.4

Print date: 10.09.2024 SDS\_NO - FN - 00000000602001207



Product name: RENOLIN ROCKDRILL 46 U

Biodegradation

**Product:** Not applicable for mixtures

Specified substance(s)

Base oil, low viscous 31 % (28 d, OECD 301F)

alkenyl amine, long-chain 66 % (28 d, OECD 301B)

12.3 Bioaccumulative potential

**Product:** Not applicable for mixtures

12.4 Mobility in soil:

**Product:** Not applicable for mixtures

12.5 Results of PBT and vPvB

assessment:

The product does not contain any substances fulfilling the PBT/vPvB crite-

ria.

12.6 Endocrine disrupting

properties

**Product:** The substance/mixture does not contain components considered to have

endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation

(EU) 2018/605 at levels of 0.1% or higher.

**12.7 Other adverse effects:** Harmful to aquatic life with long lasting effects.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

**General information:** Dispose in accordance with all applicable regulations.

**Disposal methods:** Discharge, treatment, or disposal may be subject to national, state, or local

laws.

**European Waste Codes** 

13 02 05\*: mineral-based non-chlorinated engine, gear and lubricating oils

9/11

### **SECTION 14: Transport information**

#### ADR/RID

14.1 UN number or ID number: —

14.2 UN Proper Shipping Name:

14.3 Transport Hazard Class(es)

Class: Non-dangerous goods

Label(s): – Hazard No. (ADR): –

Tunnel restriction code: -

14.4 Packing Group: –
14.5 Environmental hazards: –

Revision Date: 09.09.2024 Version: 1.4

Print date: 10.09.2024 SDS\_NO - FN - 00000000602001207



10/11

Product name: RENOLIN ROCKDRILL 46 U

14.6 Special precautions for user:

**IMDG** 

14.1 UN number or ID number: —
14.2 UN Proper Shipping Name: —

14.3 Transport Hazard Class(es)

Class: Non-dangerous goods

Label(s): -EmS No.: --

14.3 Packing Group:14.5 Environmental hazards:14.6 Special precautions for user:

**IATA** 

14.1 UN number or ID number: –
14.2 Proper Shipping Name: –

14.3 Transport Hazard Class(es):

Class: Non-dangerous goods

Label(s):

14.4 Packing Group: –
14.5 Environmental hazards: –
14.6 Special precautions for user: –

14.7 Maritime transport in bulk according to IMO instruments: Not applicable.

### **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

**EU Regulations** 

EU. Regulation 2024/590/EC on substances that deplete the ozone layer, Annex I, Controlled Substances: none

EU. Regulation 2019/1021/EU on persistent organic pollutants (POPs) (recast), as amended: none

Regulation (EC) No. 649/2012 Import and export of dangerous chemicals: none

**National Regulations** 

D-Nr. 637985

15.2 Chemical safety assessment:

No Chemical Safety Assessment has been carried out.

DIRECTIVE 2012/18/EU (SEVESO III) on the control of major-accident hazards involving dangerous substances

Not applicable

**SECTION 16: Other information** 

**Revision Information:** Vertical lines in the margin indicate an amendment.

Revision Date: 09.09.2024 Version: 1.4

Print date: 10.09.2024



Product name: RENOLIN ROCKDRILL 46 U

### Wording of the H-statements in section 2 and 3

٠,	g or this is statem	
	H225	Highly flammable liquid and vapor.
	H302	Harmful if swallowed.
	H304	May be fatal if swallowed and enters airways.
	H311	Toxic in contact with skin.
	H314	Causes severe skin burns and eye damage.
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H318	Causes serious eye damage.
	H330	Fatal if inhaled.
	H335	May cause respiratory irritation.
	H373	May cause damage to organs through prolonged or repeated expo-
		sure.
	H400	Very toxic to aquatic life.
	H410	Very toxic to aquatic life with long lasting effects.

Harmful to aquatic life with long lasting effects.

Other information:

H412

The classification complies with the current EU lists; however, it has been supplemented with expert literature information and information provided by/about our company. The following evaluation methods were used: - On the basis of test data - Calculation Method - Bridging Principle "Substantially similar mixtures" - Expert Judgement

Revision Date: Disclaimer:

09.09.2024

The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.

Revision Date: 09.09.2024 Version: 1.4

Print date: 10.09.2024