

## SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Product name:** RENOLIN UNISYN XT 320

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

**Identified uses:** Lubricant

**Uses advised against:** No uses advised against identified.

#### 1.3 Details of the supplier of the safety data sheet

**Manufacturer / Supplier** FUCHS LUBRICANTS NORWAY AS  
Fredrik Selmersvei 6  
0663 Oslo  
Norway  
**Telephone:** +47 21 99 59 50

**Contact Person:** HSE Advisor  
**E-mail:** fse-hseasc@fuchs.com  
**Telephone:** +46 8 128 25 000

**1.4 Emergency telephone number:** +47 22 59 13 00

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

The product has not been classified as hazardous, but needs to be labelled according to regulation (EU) 1272/2008 (CLP).

**Classification according to Regulation (EC) No 1272/2008 as amended.**

#### Hazard summary

**Physical Hazards:** No data available.

#### 2.2 Label Elements

EUH208: Contains alkylamine. May produce an allergic reaction.

EUH210: Safety data sheet available on request.

#### 2.3 Information on other hazards

By handling of mineral oil products and chemical products no particular hazard is known when normal precautions (item 7) and personal protective equipment (item 8) are kept. The product may not be released into the environment without control.

#### Endocrine disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**Product name:** RENOLIN UNISYN XT 320

**Results of PBT and vPvB assessment:**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**SECTION 3: Composition/information on ingredients**

**3.2 Mixtures**

**General information:** Mixture of synthetic base oils with additives.

Chemical name	Identifier	Concentration *	REACH Registration No.	Notes
alkylamine	EC: 701-175-2	0,01% - <0,10%	01-2119456798-18	

\* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

**Classification**

Chemical name	Identifier	Classification
alkylamine	EC: 701-175-2	CLP: Skin Corr. 1B;H314, Skin Sens. 1A;H317, Eye Dam. 1;H318, Aquatic Acute 1;H400, Aquatic Chronic 1;H410, Acute Tox. 4;H302, Acute Tox. 3;H311, Acute Tox. 2;H330

CLP: Regulation No. 1272/2008.

**SECTION 4: First aid measures**

**General:** Instantly remove any clothing soiled by the product.

**4.1 Description of first aid measures**

**Inhalation:** Supply fresh air; consult doctor in case of symptoms.

**Eye contact:** Promptly wash eyes with plenty of water while lifting the eye lids.

**Skin Contact:** Wash with soap and water.

**Ingestion:** Rinse mouth thoroughly.

**4.2 Most important symptoms and effects, both acute and delayed:** May cause skin and eye irritation.

**4.3 Indication of any immediate medical attention and special treatment needed:** Get medical attention if symptoms occur.

**SECTION 5: Firefighting measures**

**5.1 Extinguishing media**

**Suitable extinguishing media:** CO<sub>2</sub>, fire extinguishing powder or fog like water spraying. Extinguish larger fires with alcohol resistant foam or spray water with suitable surfactant added

**Product name:** RENOLIN UNISYN XT 320

**Unsuitable extinguishing media:** Water with a full water jet.

**5.2 Special hazards arising from the substance or mixture:** During fire, gases hazardous to health may be formed.

**5.3 Advice for firefighters**

**Special fire-fighting procedures:** Move container from fire area if it can be done without risk. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations. Collect contaminated fire fighting water separately. It must not enter drains.

**Special protective equipment for fire-fighters:** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**SECTION 6: Accidental release measures**

**6.1 Personal precautions, protective equipment and emergency procedures:** In case of spills, beware of slippery floors and surfaces.

**6.2 Environmental Precautions:** Prevent from spreading (e.g. by binding or oil barriers). Avoid release to the environment. Environmental manager must be informed of all major spillages. Prevent further leakage or spillage if safe to do so. Do not allow to enter drainage system, surface or ground water.

**6.3 Methods and material for containment and cleaning up:** Absorb with liquid-binding material (sand, diatomite, acidbinders, universal binders, sawdust). Dispose of the material collected according to regulations. Stop the flow of material, if this is without risk.

**6.4 Reference to other sections:** See Section 8 of the SDS for Personal Protective Equipment. See Section 7 for information on safe handling See Section 13 for information on disposal.

**SECTION 7: Handling and storage:**

**7.1 Precautions for safe handling:** Prevent formation of aerosols. Do not eat, drink or smoke when working with the product. Take usual precautions when handling mineral oil products or chemical products. Observe good industrial hygiene practices. Provide adequate ventilation.

**7.2 Conditions for safe storage, including any incompatibilities:** Local regulations concerning handling and storage of waterpolluting products have to be followed. Do not heat up to temperatures close to the flash point.

**7.3 Specific end use(s):** No data available.

**SECTION 8: Exposure controls/personal protection**

**8.1 Control Parameters**

**Occupational Exposure Limits**

None of the components have assigned exposure limits.

**Product name:** RENOLIN UNISYN XT 320

**8.2 Exposure controls**

**Appropriate engineering controls:** Provide adequate ventilation. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

**General information:** Wash hands before breaks and after work. Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. The usual precautionary measures should be adhered to in handling the chemicals or the mineral oil products.

**Eye/face protection:** Avoid contact with skin and eyes. Goggles/face shield are recommended. If risk of splashing, wear safety goggles or face shield.

**Skin protection**

**Hand Protection:** Material: Nitrile butyl rubber (NBR).  
Min. Breakthrough time: >= 480 min  
Recommended thickness of the material: >= 0,38 mm

Avoid long-term and repeated skin contact. Suitable gloves can be recommended by the glove supplier. Use skin protection cream for preventive skin protection. Protective gloves, where permitted in acc. to safety directions. The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Other:** Do not carry cleaning cloths impregnated with the product in trouser pockets. Wear suitable protective clothing.

**Respiratory Protection:** Ensure good ventilation/exhaustion at the workplace. Avoid breathing vapour/ aerosol.

**Thermal hazards:** Not known.

**Hygiene measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing to remove contaminants. Discard contaminated footwear that cannot be cleaned.

**Environmental Controls:** No data available.

**SECTION 9: Physical and chemical properties**

**9.1 Information on basic physical and chemical properties**

**Appearance**

**Physical state:** liquid  
**Form:** liquid  
**Color:** Pale yellow  
**Odor:** Characteristic  
**pH:** substance/mixture is non-soluble (in water)

**Product name:** RENOLIN UNISYN XT 320

<b>Freezing point:</b>	not determined
<b>Boiling Point:</b>	not determined
<b>Flash Point:</b>	242 °C
<b>Flammability (solid, gas):</b>	not determined
<b>Explosion Limit - Upper (%):</b>	Not applicable for mixtures
<b>Explosion Limit - Lower (%):</b>	Not applicable for mixtures
<b>Vapor pressure:</b>	Not applicable for mixtures
<b>Relative vapor density:</b>	Not applicable for mixtures
<b>Density:</b>	0,85 g/ml (15,00 °C)
<b>Solubility(ies)</b>	
<b>Solubility in Water:</b>	Insoluble in water
<b>Solubility (other):</b>	No data available.
<b>Partition coefficient (n-octanol/water):</b>	Not applicable for mixtures
<b>Auto-ignition temperature:</b>	not determined
<b>Decomposition Temperature:</b>	not determined
<b>Kinematic viscosity:</b>	320 mm <sup>2</sup> /s (40 °C)
<b>Particle characteristics:</b>	Not applicable
<b>9.2 Other information</b>	No data available.

**SECTION 10: Stability and reactivity**

<b>10.1 Reactivity:</b>	Stable under normal use conditions.
<b>10.2 Chemical Stability:</b>	Stable under normal use conditions.
<b>10.3 Possibility of hazardous reactions:</b>	Stable under normal use conditions.
<b>10.4 Conditions to avoid:</b>	Stable under normal use conditions.
<b>10.5 Incompatible Materials:</b>	Strong oxidizing substances. Strong acids. Strong bases.
<b>10.6 Hazardous Decomposition Products:</b>	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapors.

**SECTION 11: Toxicological information**

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity**

**Oral**

**Product:** Not classified for acute toxicity based on available data.

**Specified substance(s)**

alkylamine LD 50 (Rat): 612 mg/kg (OECD 401)

**Product name:** RENOLIN UNISYN XT 320

---

## **Dermal**

**Product:** Not classified for acute toxicity based on available data.

## **Specified substance(s)**

alkylamine LD 50 (Rat): 251 mg/kg (OECD 402)

## **Inhalation**

**Product:** Not classified for acute toxicity based on available data.

## **Specified substance(s)**

alkylamine LC 50 (Rat, 4 h): 1,19 mg/l (OECD 403) Vapour

## **Skin Corrosion/Irritation:**

**Product:** Based on available data, the classification criteria are not met.

## **Serious Eye Damage/Eye Irritation:**

**Product:** Based on available data, the classification criteria are not met.

## **Respiratory or Skin Sensitization:**

**Product:** Skin sensitizer: Based on available data, the classification criteria are not met.

Respiratory sensitizer: Based on available data, the classification criteria are not met.

## **Germ Cell Mutagenicity**

**Product:** Based on available data, the classification criteria are not met.

## **Carcinogenicity**

**Product:** Based on available data, the classification criteria are not met.

## **Reproductive toxicity**

**Product:** Based on available data, the classification criteria are not met.

## **Specific Target Organ Toxicity - Single Exposure**

**Product:** Based on available data, the classification criteria are not met.

## **Specific Target Organ Toxicity - Repeated Exposure**

**Product:** Based on available data, the classification criteria are not met.

## **Aspiration Hazard**

**Product:** Based on available data, the classification criteria are not met.

## **11.2 Information on other hazards**

### **Endocrine disrupting properties**

**Product:** The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**Product name:** RENOLIN UNISYN XT 320

**SECTION 12: Ecological information**

**Acute toxicity**

**Product:** Based on available data, the classification criteria are not met.

**Fish**

**Specified substance(s)**  
alkylamine LL 50 (Fish, 96 h): 1,3 mg/l

**Aquatic Invertebrates**

**Specified substance(s)**  
alkylamine EL50 (Water Flea, 48 h): 2,5 mg/l

**Chronic ToxicityProduct:** Based on available data, the classification criteria are not met.

**Fish**

**Specified substance(s)**  
alkylamine NOEC (Fish, 96 d): 0,078 mg/l

**Toxicity to Aquatic Plants**

**Specified substance(s)**  
alkylamine ErC50 (Alga, 72 h): 0,44 mg/l

**12.2 Persistence and Degradability**

**Biodegradation**

**Product:** Not applicable for mixtures  
**Specified substance(s)**  
alkylamine 21,8 % (28 d, OECD 301D) Not easily biodegradable

**12.3 Bioaccumulative potential**

**Product:** Not applicable for mixtures

**12.4 Mobility in soil:**

**Product:** Not applicable for mixtures

**12.5 Results of PBT and vPvB assessment:**

The product does not contain any substances fulfilling the PBT/vPvB criteria.

**12.6 Endocrine disrupting properties**

**Product:** The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**12.7 Other adverse effects:** No data available.

**Product name:** RENOLIN UNISYN XT 320

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**General information:** Dispose in accordance with all applicable regulations.

**Disposal methods:** Do not empty into drains; dispose of this material and its container in a safe way. When storing used products, ensure that the waste categories and mixing instructions are observed.

**European Waste Codes**

13 02 06\*: synthetic engine, gear and lubricating oils

**SECTION 14: Transport information**

**ADR/RID**

- 14.1 UN number or ID number: —
- 14.2 UN Proper Shipping Name: —
- 14.3 Transport Hazard Class(es)
  - Class: Non-dangerous goods
  - Label(s): —
  - Hazard No. (ADR): —
  - Tunnel restriction code: —
- 14.4 Packing Group: —
- 14.5 Environmental hazards: —
- 14.6 Special precautions for user: —

**IMDG**

- 14.1 UN number or ID number: —
- 14.2 UN Proper Shipping Name: —
- 14.3 Transport Hazard Class(es)
  - Class: Non-dangerous goods
  - Label(s): —
  - EmS No.: —
- 14.3 Packing Group: —
- 14.5 Environmental hazards: —
- 14.6 Special precautions for user: —

**IATA**

- 14.1 UN number or ID number: —
- 14.2 Proper Shipping Name: —
- 14.3 Transport Hazard Class(es):
  - Class: Non-dangerous goods
  - Label(s): —
- 14.4 Packing Group: —
- 14.5 Environmental hazards: —
- 14.6 Special precautions for user: —

**14.7 Maritime transport in bulk according to IMO instruments:** Not applicable.



**Product name:** RENOLIN UNISYN XT 320

**SECTION 15: Regulatory information**

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

**EU Regulations**

**EU. Regulation 2024/590/EC on substances that deplete the ozone layer, Annex I, Controlled Substances:** none

**EU. Regulation 2019/1021/EU on persistent organic pollutants (POPs) (recast), as amended:** none

**15.2 Chemical safety assessment:**

No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information**

**Revision Information:** Vertical lines in the margin indicate an amendment.

**Wording of the H-statements in section 2 and 3**

H302	Harmful if swallowed.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

**Other information:** The classification complies with the current EU lists; however, it has been supplemented with expert literature information and information provided by/about our company. The following evaluation methods were used: - On the basis of test data - Calculation Method - Bridging Principle "Substantially similar mixtures" - Expert Judgement

**Revision Date:** 26.08.2024

**Disclaimer:** The data contained in this safety data sheet are based on our current knowledge and experience and are given to the best of our knowledge and belief. It characterizes the product only with regard to safety requirements for handling, transport and disposal. The data do not describe the product's properties (tech. product specification). Neither should any agreed property nor the suitability of the product for any specific technical application be deduced from the data contained in this safety data sheet. Modifications on this document are not allowed. The data are not transferable to other products. In the case of mixing the product with other products or in the case of processing, the data in this safety data sheet are not necessarily valid for the new-made material. It is the responsibility of the recipient of the product to observe federal, state and local law. Please contact us to obtain up-to-date safety data sheets. This document was issued electronically and has no signature.