

# LUBRICANTS FOR JAGUAR LAND ROVER PASSENGER CARS



Quality counts. As one of the leading factory fill specialists we supply high performance quality. Today and tomorrow. Therefore JAGUAR LAND ROVER counts on lubricants and specialities of FUCHS.

Product	Description	Specifications	Approvals	FUCHS Recommendations
<b>Engine Oils</b>				
<b>TTAN</b> GT1 EVO SAE 0W-20  <b>XTL</b> <sup>®</sup> TECHNOLOGY	Premium Performance Engine Oil with new XTL <sup>®</sup> -Technology in path-breaking viscosity class. Specially designed for highly stressed downsized engines with maximum power output, for extreme fuel-economy characteristics and reduced CO <sub>2</sub> emissions. Excellent cold starting behaviour, very fast oil circulation and outstanding performance reserves.	ACEA A1/B1	JAGUAR LAND ROVER STJLR.51.5122	–
<b>TTAN</b> GT1 LL-12 FE SAE 0W-30  <b>XTL</b> <sup>®</sup> TECHNOLOGY	Premium Performance Engine Oil with new XTL <sup>®</sup> -Technology. Specially developed for latest gasoline and diesel vehicles with exhaust after treatment. Excellent cold starting, lower oil consumption and outstanding performance reserves.	ACEA C2	–	JAGUAR LAND ROVER STJLR.03.5007
<b>TTAN</b> GT1 PRO C-1 SAE 5W-30	Premium Performance, extreme fuel-economy engine oil for modern passenger cars and light commercial vehicles with or without extended service intervals. Specially developed for vehicles with exhaust after treatment and turbocharger. Optimum cold starting, lower oil consumption and minimized exhaust emissions.	ACEA C1	JAGUAR LAND ROVER STJLR.03.5005	FORD WSS-M2C934-B
<b>TTAN</b> Supersyn LONGLIFE SAE 5W-40	Ultra High Performance, fuel-economy engine oil for a variety of vehicles with or without extended service intervals. Optimum cold starting and lower oil consumption.	ACEA A3/B4 API SN/SM	–	–
<b>TTAN</b> Supersyn F Eco-B SAE 5W-20	Ultra High Performance, extreme fuel-economy engine oil. Optimum cold starting and lower oil consumption.	ACEA A1/B1 API SN FORD WSS-M2C948-B	JAGUAR LAND ROVER STJLR.03.5004	–
<b>TTAN</b> Supersyn F Eco-DT SAE 5W-30	Ultra High Performance, extreme fuel-economy engine oil. Optimum cold starting and lower oil consumption.	ACEA A1/B1 ACEA A5/B5 API SL FORD WSS-M2C913-C FORD WSS-M2C913-D	JAGUAR LAND ROVER STJLR.03.5003	JAGUAR M2C913-B FORD WSS-M2C913-A FORD WSS-M2C913-B
<b>Gear Oils</b>				
<b>TTAN</b> SINTOFLUID SAE 75W-80	Premium Performance Manual Transmission Fluid for passenger cars. Offering good gearbox efficiency. Suitable as fill for life fluid according to manufacturer.	API GL-5	–	FORD WSS-M2C200-C3
<b>TTAN</b> SINTOPOID LS SAE 75W-90	Premium Performance, fully-synthetic multifunctional gear oil, formulated with fully-synthetic base oils. Suitable for axles and transfer gear-boxes with or without self-locking differentials and also as trouble shooter for conventional manual transmissions.	API GL-4/-5/-5 incl. LS	–	FORD WSS-M2C200-C/C2
<b>Automatic Transmission Fluids (ATF)</b>				
<b>TTAN</b> TITAN ATF 6000 SL	Premium Performance ATF offering maximum performance in passenger car applications such as automatic transmissions with torque converters or wet clutches as well as power steering systems. Formulation is licensed according to DEXRON VI and downwards compatible to any former DEXRON-specification. Product dyeing: red.	–	DEXRON VI	–
<b>TTAN</b> TITAN ATF 4400	Ultra High Performance ATF specifically formulated for Japanese passenger cars and light commercial vehicles, as well as for several European and American manufacturers. The high torque capacity exceeds the performance of many original fluids. Product dyeing: red.	–	–	DEXRON III AISIN WARNER/AW-1 FORD MERCON FORD M2C924-A/ M2C922-A1 JWS 3309/TYP T-IV

Product	Description	Specifications	Approvals	FUCHS Recommendations
<b>Double Clutch Transmission Fluids (DCTF)</b>				
<b>PENTOSIN</b> <b>PENTOSIN FFL-3</b>	Premium Performance DCTF. Specially developed for ZF/ Porsche Double Clutch Transmission with wet clutch. Provides optimum wear protection and excellent friction properties even under hard conditions and offers best shifting performance over the whole lifetime.	–	ZF TE-ML 11 (ZF001747)	JAGUAR LAND ROVER GX73-M1R564-AA
<b>Central Hydraulic / Power Steering Fluids</b>				
<b>PENTOSIN</b> <b>PENTOSIN CHF 202</b>	Premium Performance Power Steering and Central Hydraulic Fluid with a wide application and approval profile for various manufacturers. Product dyeing: green.	FORD M2C204-A2	–	LAND ROVER LR003401
<b>Antifreeze</b>				
<b>MAINTAIN</b> <b>FRICOFIN LL</b>	Premium Performance Coolant Additive based on monoethylene glycol. Free from nitrite, amine, phosphate and silicates. Product dyeing: orange.	ASTM D 3306 TYPE I ASTM D 6210 TYPE I-FF BS 6580:2010 SAE J814 FORD WSS-M97-B44-D JAGUAR LAND ROVER STJLR.651.5003	–	–
<b>Brake Fluids</b>				
<b>MAINTAIN</b> <b>MAINTAIN DOT 4</b>	Super High Performance Brake Fluid for hydraulic brake systems and clutch actuation in passenger cars, trucks and motorcycles.	FMVSS NR. 116 DOT 3/ DOT 4 ISO 4925 CLASS 3/4 SAE J1703/J1704	–	–

The information contained in this product information is based on the experience and know-how of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircraft/spacecrafts or their components, unless such products are removed before the components are assembled into the aircraft/spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH.  
© FUCHS SCHMIERSTOFFE GMBH. All rights reserved. Edition 02/2018

## FUCHS SCHMIERSTOFFE GMBH

Export Division ■ Friesenheimer Straße 19 ■ 68169 Mannheim/Germany

Phone: +49 621 3701-1703 ■ Fax: +49 621 3701-7719

E-Mail: [export@fuchs-schmierstoffe.de](mailto:export@fuchs-schmierstoffe.de) ■ [www.fuchs.com/de/en](http://www.fuchs.com/de/en)