


FUCHS Industrial Lubricants

Innovative lubricants need experienced application engineers

Every lubricant change should be preceded by expert consultation on the application in question. Only then can the best lubricant system be selected. Experienced FUCHS engineers will be glad to advise on products for the application in question and also on our full range of lubricants.



Contact:



FUCHS EUROPE SCHMIERSTOFFE GMBH

Friesenheimer Straße 15
68169 Mannheim / Germany
Phone: +49 621 3701-0
Fax: +49 621 3701-570
E-mail: zentrale@fuchs-europe.de
www.fuchs-europe.de

Export Division
Friesenheimer Straße 9
68169 Mannheim / Germany
Phone: +49 621 3701-703
Fax: +49 621 3701-719

bloesch-partner.de 07/2008 1.0

FUCHS Industrial Lubricants



For extra process reliability



Process media
for the manufacturing
of white goods



GLOBAL PARTNER



HOW WE EXCEL

We are a German company whose almost 600 employees manufacture and market a wide range of lubricants and derived specialties. The company, which was founded in 1931 as RUDOLF FUCHS, is located in Mannheim and is a 100 % subsidiary of FUCHS PETROLUB AG, which is the largest independent lubricants manufacturer worldwide.

Our company's degree of specialisation and innovation is way above the industrial average in this field. The full product line includes almost 2,000 lubricants and derived specialties for all walks of life, industrial processes and applications. Our customer's success is also our success. Because partnership to us means passing-on benefits.

The advantage of a strong market presence: FUCHS is the largest independent manufacturer of lubricants in the world. The benefit of premium, innovative products from a full-line manufacturer: With a complete product line as well as tailor-made special solutions, FUCHS has a product for every application. The benefits of reliability: Certified according to DIN EN ISO 9001:2000 and ISO/TS 16949:2002, FUCHS has been continuously upgrading its highly specialised lubricants for decades.

And naturally, partnership for us also means providing our customers with competent support. With comprehensive marketing. With high-performance logistics. With the development of successful service concepts. And qualified consulting. Because together, we can achieve more.

WHAT INCREASES THE VALUE OF OUR PRODUCTS

We develop lubricants: application-specific and tailor-made for our customer's processes. Together we look for the best lubricants for our customers. This cooperation is unique in terms of its form, scope and intensity. **We call it development partnership.** The success of our development partnerships is based on an important fact: FUCHS is not one of the oil-giants.

FUCHS is a multinational, independent lubricant manufacturer. Our independence is the difference. We are open to new solutions, open for visions – the prerequisites for innovations. And innovation is the defining characteristic of FUCHS. 70 % of our products are less than five years old and the great majority of our products are individual solutions. Challenge us and see!



DIN EN ISO 9001:2000
ISO/TS 16949:2002
DIN EN ISO 14001:2004
REG.NR. 2476



Process media for the manufacturing of white goods.

Corrosion protection in steel mills



Our thixotropic corrosion protection oils, prelubes and hotmelts can be applied in-house by the steel mills.

Forming



The formation of an effective barrier between the material and the

The complete lubricants program from the specialists.

All from one supplier

The manufacturing of pressed panels and parts involves a large number of complex steps. These steps are inter-dependent on each other and carefully matched. And, in particular, the lubricants used have to guarantee optimum compatibility throughout the process. This leaflet provides an overview of the full line of products offered FUCHS.

Cross-compatibility is constantly monitored in our own, state-of-the-art research facilities and laboratories.

This guarantees a reliable process chain starting with cleaning, to metalworking, through to corrosion protection.

As well as constant monitoring, we regularly add new products to our program.

Apart from conventional products and solutions, we also offer products which conform to national environmental legislation and/or VOC regulations.

Decades of experience, far-reaching know-how, global approvals from leading manufacturers and our local experts make our product program unique.

The benefits of FUCHS system products:

- Intensive consultation, optimum service – worldwide
- Full range of products – all from one supplier
- Fully compatible products
- No process failures caused by product incompatibility
- Thorough testing in in-house facilities
- Close cooperation in obtaining approvals

For optimum process reliability.

Corrosion protection oil

ANTICORIT RP 4107 S Standard corrosion preventive used by European steel manufacturers. Approved by the German VDA.

Prelube

ANTICORIT PL 3802-39 S Thixotropic corrosion preventive with outstanding drawing properties. Approved by the German VDA.

Hotmelt

ANTICORIT PL 39 SX Highly thixotropic, waxy corrosion preventive with outstanding drawing properties. Fulfills German VDA 230-202.

Water-miscible

RENOFORM MBW SERIES Emulsifiable forming lubricants for all materials.

RENOFORM MBO 2755 SD Water-miscible, synthetic forming lubricant for all materials.

RENOFORM HFL SERIES Dry-film lubricants, water-based dispersions for all materials.

While the information and figures given here are typical of current production and confirm to specification, minor variations may occur. Subject to amendment.
Edition 07/2008



The optimum lubricant for every process stage.



the tool requires lubricants with outstanding performance.

Forming oil: stamping, drawing and pressing

Non water-miscible (volatile)

RENOFORM UBO SERIES	Annealing residue-free forming oils. Volatile at room temperature. Contains VOC*. For all materials.
RENOFORM LVO SERIES	Annealing residue-free forming oils. Volatile at room temperature. VOC*-free. For all materials.
RENOFORM HBO 1514	Annealing residue-free, high-performance forming oils. Volatile at room temperature. Contains VOC*. For steel and stainless steel.

*VOC = Volatile Organic Compounds.

Non water-miscible (containing mineral oil)

RENOFORM MBO SERIES	Mineral oil-based forming lubricants for all materials (chlorine-free).
RENOFORM HBO SERIES	Very high-performance, mineral oil-based forming lubricants for steel and stainless steel (chlorine-free).
RENOFORM HBX-60	High-performance hotmelt with outstanding anti-wear properties for steel and stainless steel (chlorine-free).
RENOFORM MZAN SERIES	High performance cold extrusion oils especially formulated for stainless steel (contains chlorine).

Non water-miscible (mineral oil-free)

PLANTOFORM SERIES	Synthetic forming oils for aluminium and copper (biodegradable).
--------------------------	--

We offer a large number of drawing lubricants ranging from low to high-viscosity and containing various additive packages. The selection of the most suitable drawing lubricant depends on the type and difficulty of the application along with lubricant application method.

While the information and figures given here are typical of current production and confirm to specification, minor variations may occur. Subject to amendment. Edition 07/2008

Cleaning



Surfaces for subsequent manufacturing processes may have to be oil-free and clean. A number of different types of cleaners are available.

Solvent cleaners

RENOCLEAN UWF	Solvent cleaner. Free of aromatics. Contains VOC*.
RENOCLEAN KU	Odor-optimized, solvent cleaner. Free of aromatics. Contains VOC*.
RENOCLEAN KLV	VOC*-free, universal solvent-based cleaner. Perfect for industrial, workshop and domestic applications.

Water-based alkaline (sprayable cleaners)

RENOCLEAN VR 1021 SERIES	Medium-alkalinity. For use at temperatures between +35 °C and +60 °C.
---------------------------------	---

Water-based alkaline (submersion cleaners)

RENOCLEAN SPEZIAL 2000	Medium-alkalinity. Universal application such as components, floors, etc.
RENOCLEAN VR 1798/2	Medium-alkalinity. Universally suitable for steel and aluminium. Also for ultrasonic cleaners.

*VOC = Volatile Organic Compounds.

Corrosion protection



Corrosion protection is generally specified for storage and transport.

Dewatering fluids

ANTICORIT DF SERIES	High-speed dewatering fluids. Form thin, highly-effective, oily-, waxy- or lacquer-like films. Also available in versions without film-forming agents exclusively for stain-free drying.
----------------------------	--

Corrosion protection

ANTICORIT OHK SERIES	Corrosion protection concentrates and ready-to-use versions with white spirit, isoparaffins and oils to protect all metals. Outstanding fingerprint-remover properties.
-----------------------------	---

Water-miscible

ANTICORIT MKR SERIES	Water-miscible corrosion preventives for the cleaning and interim protection of semi-finished components, phosphated parts and components used in the potable water sector. Also an additive for hydraulic water and coolant.
ANTICORIT SKR SERIES	Water-miscible, mineral oil-free and low-foaming additives for cooling and hydraulic water.

Vapour phase inhibitors

ANTICORIT VCI SERIES	Advanced VCI technology for the protection of all metals. Available as VCI paper, film, powder, tablets or oils. Tailor-made solutions for corrosion protection and packaging.
-----------------------------	--

A wide range of films are available ranging from oily to vaseline-like and wax-like. If a film is not required, we can solve your corrosion protection problems with our comprehensive VCI line of products. This includes paper, films, tablets, foams and many other special solutions.

While the information and figures given here are typical of current production and confirm to specification, minor variations may occur. Subject to amendment. Edition 07/2008

Ask the specialists:

The FUCHS check list for a product recommendation.

Based on this questionnaire, we can tell you which is the best lubricant for your particular needs.

Your address

Company/customer: _____ Phone: _____
Street: _____ Fax: _____
City: _____ E-mail: _____
Contact/function/dept.: _____

Which product do you currently use?

Forming lubricant: _____
Cleaner: _____
Corrosion protection: _____

Forming

Material (blank): ☐ Steel ☐ Stainless steel ☐ Aluminium ☐ Nonferrous metal
☐ Other: _____
Material thickness: $s_0 =$ _____ mm

Tool: _____ Material: _____ Coating: _____

Machine: _____ Manufacturer: _____ Type: _____

Specification of the desired forming lubricant:

☐ Mineral oil-based ☐ Chlorine-free ☐ Corrosion protection
☐ Synthetic ☐ Pigments

Viscosity at +40 °C: $\nu_{40} =$ _____ mm²/s Concentration: _____ %

Application:

☐ Spraying on the material ☐ Run-off
☐ Spraying the tool ☐ Flooding

☐ Other: _____

Simply copy, complete – as far as possible –
and fax back to +49 621 3701-414.

Cleaning

Process: ☐ Dipping ☐ Spraying ☐ Flooding ☐ Other: _____
Type: ☐ Water-based ☐ Acidic ☐ Alkaline ☐ Neutral ☐ Other: _____
Washing: Wash temperature: _____ °C pH-value: _____ Duration: _____ s, min, hr
Storage: Type of storage: _____ Duration: _____ Days, Weeks
Subsequent processes: _____

Corrosion protection

Packing: ☐ None ☐ In μm PE film ☐ Individual packaging ☐ Closed packaging
☐ In greaseproof paper ☐ In μm VCI film ☐ In racks ☐ Open packaging
☐ With VCI ☐ On greaseproof paper ☐ Other: _____
Transport: ☐ No transport ☐ National ☐ Sea freight on deck
☐ Regional ☐ Within Europe ☐ Sea freight below deck
Storage condition: ☐ Warehouse ☐ Tropical climate ☐ Cold climate ☐ Temperature: _____ °C
☐ Shed ☐ Subtropical climate ☐ Monsoon conditions ☐ Humidity: _____ %
☐ Outdoors ☐ Temperate climate ☐ Coastal region ☐ Other: _____
Required corrosion protection duration: ☐ Up to 1 week ☐ Up to 3 month ☐ Up to 1 year ☐ Up to 3 year
☐ Up to 1 month ☐ Up to 6 month ☐ Up to 1 1/2 year ☐ Over 5 year
Film type: ☐ No film ☐ Waxy ☐ < 2 μm ☐ > 5 μm
☐ Oily ☐ Vaseline-like ☐ 2 – 5 μm ☐ _____
Characteristics of the corrosion preventive: ☐ Non-thixotropic ☐ With VCI inhibitors ☐ Solvent FP < +61 °C ☐ Water-based
☐ Thixotropic ☐ VOC-free solvent ☐ Solvent FP > +61 °C ☐ Barium-free
Application: ☐ Dipping ☐ Hot application ☐ Temperature: _____ °C
☐ Spraying ☐ Drying possible ☐ Other: _____

Supplementary comments:

Signature: _____ Date: _____