

Lube Cube Availability

RENOLIN B RANGE



All of the below products hold the following manufacturer approvals:

BOSCH REXROTH **CINCINNATI MILACRON** **DENISON**

SAUER DANFOSS **US STEEL** **VICKERS**

Product	Available Lube Cube size(s)		Density at 15°C kg/m ³	Flash point Clev. °C	Kin. visc. at 40°C mm ² /s	Kin. visc. at 100°C mm ² /s	VI	Pour point °C	Specifications
	5L	20L							
RENOLIN B 1 VG 5		•	837	130	5	1.7	-	-20	DIN 51524-2:HLP ISO 6743-4: HM
RENOLIN B 3 VG 10		•	850	178	10	2.6	95	-42	
RENOLIN B 5 VG 22		•	863	200	22	4.4	107	-27	
RENOLIN B 10 VG 32	•	•	876	205	32	5.5	109	-24	
RENOLIN B 11 VG 37		•	875	208	37	6.2	103	-31	
RENOLIN B 15 VG 46	•	•	875	210	46	6.9	105	-24	
RENOLIN B 20 VG 68	•	•	881	224	68	8.8	100	-24	
RENOLIN B 30 VG 100		•	883	232	100	11.1	96	-18	
RENOLIN B 40 VG 150		•	887	224	150	14.5	94	-15	
RENOLIN B 15 HVI		•	859	180	15	3.8	151	-45	DIN 51524-3, HVLP ISO 6743-4, HV ISO 11158
RENOLIN B 32 HVI		•	871	178	32	6.3	152	-48	
RENOLIN B 46 HVI	•	•	879	186	46	8.1	150	-45	
RENOLIN B 68 HVI		•	868	240	68	11	153	-36	

FUCHS LUBRICANTS (UK) plc,

New Century Street, Hanley, Stoke on Trent, ST1 5HU.

Phone: +44 (0) 1782 203700 | E-Mail: contact-uk@fuchs.com | www.fuchs.com/uk

[f](https://www.facebook.com/fuchslubricantsuk) /fuchslubricantsuk [@fuchslube_uk](https://twitter.com/fuchslube_uk) [in](https://www.linkedin.com/company/fuchs-lubricants-uk-plc) /fuchs-lubricants-uk-plc