

## CASSIDA GREASE RLS Series

Synthetic regular load greases for food and beverage processing equipment

### Performance Features

- Noted for their long life
- Good water resistance ensures lasting protection even in the presence of large amounts of water
- Good oxidation and mechanical stability. Resists the formation of deposits caused by oxidation at high operating temperatures and maintain consistency, reducing leakage
- Effective corrosion protection. Ensures components/ bearings do not fail due to corrosion
- Good adhesive properties reduce losses thereby reducing grease consumption
- Neutral odour and taste



Gears -  
enclosed



Roller bearings



Partner  
Programme



Partner  
Programme



NSF registered

### Certifications and Specifications

- NSF H1
- NSF ISO 21469
- Kosher
- Halal

### Description

CASSIDA GREASE RLS 00, 0, 1 and 2 are specially developed for the grease lubrication of machinery in the food and beverage processing and packaging industry. They are based on an aluminium complex thickener, synthetic fluids and selected additives chosen for their ability to meet the stringent requirements of the food and beverage industry. Certified by NSF for ISO 21469 and registered by NSF (Class H1) for use where there is potential for incidental food contact. Produced according to FLT Quality Standards, in facilities where HACCP audit and Good

# CASSIDA Product Information



**LUBRITECH**  
Special Application Lubricants

Manufacturing Practice have been implemented and form part of the quality and hygiene management systems ISO 9001 and ISO 21469.

## Applications

- Lightly loaded grease lubricated gear boxes (RLS 00/0)
- Automatic, centralised lubrication systems (RLS 00/0)
- Rolling element and plain bearings (RLS 1/2)
- Joints and linkages open to the atmosphere (RLS 1/2)
- Automatic, centralised lubrication systems (RLS 1/2)

## Seal and Paint Compatibility

Compatible with the elastomers, gaskets, seals and paints normally used in food machinery lubrication systems.

## Handling and Storage

All food grade lubricants should be stored separately from other lubricants, chemical substances and foodstuffs and out of direct sunlight or other heat sources. Store between 0 °C and +40 °C. Provided that the product has been stored under these conditions we recommend that the product be used within 3 years from the date of manufacture. Upon opening a pack, the product must be used within 2 years (or within 3 years of date of manufacture, whichever is the sooner).

# CASSIDA Product Information



**LUBRITECH**  
Special Application Lubricants

## Technical Data: CASSIDA GREASE

<u>Characteristics</u>	<u>RLS 00</u>	<u>RLS 0</u>	<u>RLS 1</u>	<u>RLS 2</u>	<u>Unit</u>	<u>Test Method</u>
NSF Reg. No.	144705	144704	144706	144707		
Colour	White	White	White	White		
Structure	Semi-fluid	Semi-fluid	Smooth paste	Smooth paste		
NLGI grade	00	0	1	2		DIN 51818
Type of thickener	Aluminium Complex	Aluminium Complex	Aluminium Complex	Aluminium Complex		
Worked penetration [+25 °C]	400 - 430	355 - 385	310 - 340	265 - 295	1/10 mm	ISO 2137
Kin. Visc. (base oil) at +40 °C	100	150	150	150	mm <sup>2</sup> /s	ISO 3104
Kin. Visc. (base oil) at +100 °C	13,4	18,0	18,0	18,0	mm <sup>2</sup> /s	ISO 3104
Dropping point	>200	>240	>240	>240	° C	ISO 2176
Operating temperatures	-45 to +100	-40 to +100	-40 to +120	-35 to +120	° C	LLS 134
short-term peak	+120	+120	+140	+140	° C	
Classification DIN	GP HC 00 G-40	GP HC 0 G-40	KP HC 1 K-40	KP HC 2 K-30		DIN 51502
Classification ISO	L-XEBEA 00	L-XDBEA 0	L-XDCEA 1	L-XCCEA 2		ISO 6743-9

LLS = LUBRITECH Laboratory Specification  
Typical for current production. Variations in these characteristics may occur.

As far as we know this information reflects the current state of knowledge and our research. It cannot, however, be taken as an assurance about the properties nor as a guarantee of the suitability of the product for the individual case in point. Before using our products the purchaser must, therefore, check their suitability and be satisfied that the output will be satisfactory. Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without prior announcement, unless otherwise provided in customer-specific agreements. With the publication of this product information sheet, all previous editions cease to be valid.

We are specialized in developing products for extreme tribological problems in cooperation with end users. FUCHS LUBRITECH provides service and individual advice. Please contact us!  
E-Mail: [info@fuchs-lubritech.de](mailto:info@fuchs-lubritech.de)