

# Product Information

MOVING YOUR WORLD



## ANTICORIT WRC PJ204

### Description

Part of the FUCHS range of wire rope lubricants.

Mineral hydrocarbon wax based product, formulated with performance enhancing properties for wire rope protection. Before application, the product is heated and leaves a protective, soft grease-like layer when cooled.

### Application

Formulated primarily for use in the manufacture of Mining (lock coil ropes).

### Advantages/Benefits

- Excellent corrosion resistance (passes 720 hours salt water test - ASTM B117)
- High melting point
- Evenly distributed coverage
- Excellent core penetration
- Good sealing properties
- Good corrosion protection

# Product Information

MOVING YOUR WORLD



## CHARACTERISTICS: ANTICORIT WRC PJ204

Characteristics	Unit	Value	Test Method
Base		PJ	
Colour		Brown	
Drop Point	°C	100 min. 109 typical	IP371
Break Point	°C	-35	IP80
Flash Point PMOC	°C	220 min	
Penetration Cone at 25°C unworked	1/10 mm	120 typical	IP179 (Set from mol-ten)
Salt Water Corrosion after 720 hours		Pass	ASTM B117
Application Temperature	°C	115 to 120	
Viscosity at 100°C	cP	200 typical	
Bitumen Free		YES	

### Notes

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS (UK) plc in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible.

Our products must not be used in aircraft or spacecraft. Our products may be used in manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft.

The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS (UK) plc application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS (UK) plc.

© FUCHS LUBRICANTS (UK) plc. All Rights reserved.

PM3-UK IND Mar 24 Page 2 of 2