

# Product Information

*MOVING YOUR WORLD*



## ANTICORIT WRC PJ207

### Description

Part of the FUCHS range of wire rope lubricants.

Designed to help preserve and lubricate wire ropes, particularly in marine and offshore applications. Produced from a variety of waxes, mineral oils and additives to enhance performance. Offers outstanding corrosion protection, even under humid and salt water conditions.

### Application

Formulated primarily for use in the manufacture of Marine / Offshore ropes, but also suitable for use in the manufacture of Drilling ropes..

### Advantages/Benefits

- Flexible at low temperatures
- Excellent corrosion protection
- Temperature range (-25°C to 65°C)
- Compatible with LDPE, MDPE, HDPE

# Product Information

MOVING YOUR WORLD



## CHARACTERISTICS: ANTICORIT WRC PJ207

Base		PJ	
Colour		Black	
Drop Point	°C	85 min. 99 typical	IP371
Break Point	°C	-30	IP80
Flash Point PMOC	°C	200 min.	
Penetration Cone at 25°C unworked	1/10 mm	50 to 70	IP50
Cyclic Humidity Test after 720 hours		Pass (2500 hrs)	ASTM B117
Salt Water Corrosion after 720 hours		Pass (2500 hrs)	ASTM B117
Coefficient of Friction (μ)		0.1	SRV
Application Temperature	°C	115 to 125	
Bitumen Free		YES	

### Notes

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS (UK) plc in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible.

Our products must not be used in aircraft or spacecraft. Our products may be used in manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft.

The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS (UK) plc application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS (UK) plc.

© FUCHS LUBRICANTS (UK) plc. All Rights reserved.