

ANTICORIT WRC PJ33

Description

Part of the FUCHS range of wire rope lubricants.

Mineral hydrocarbon wax based product that contains additives to enhance performance. A cost effective, general purpose rope lubricant designed to preserve and lubricate wire ropes. Can be applied either during manufacture or as a service dressing.

Application

Formulated primarily for use in the manufacture of General Purpose - Engineering ropes.

Advantages/Benefits

- Cost effective
- For use during manufacture or in service

PM3-UK IND Sept 24 Page 1 of 2

FUCHS LUBRICANTS (UK) plc New Century Street, Hanley Stoke-on-Trent, Staffordshire, ST1 5HU Phone +44 (0) 1782 203700 Fax +44 (0) 1782 202073 contact- uk@fuchs.com





CHARACTERISTICS: ANTICORIT WRC PJ33

Base		PJ	
Colour		Brown	
Drop Point	°C	65 min. 78 typical	IP371
Break Point	°C	-30	IP80
Flash Point PMOC	٥C	220 min.	
Penetration Cone at 25°C unworked	1/10 mm	85 to 115	IP50
Application Temperature	٥C	80 to 100	
Bitumen Free		YES	

Notes

The information contained in this product information is based on the experience and know-how of FUCHS LUBRICANTS (UK) plc in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally valid statements about the function of our products are not possible.

Our products must not be used in aircraft or spacecraft. Our products may be used in manufacture of components for aircraft or spacecraft if they are removed without residue from the components prior to assembly into the aircraft or spacecraft.

The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application. We therefore recommend that you consult a FUCHS LUBRICANTS (UK) plc application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid. Any form of reproduction requires express prior written permission from FUCHS LUBRICANTS (UK) plc.

© FUCHS LUBRICANTS (UK) plc. All Rights reserved.

PM3-UK IND Sept 24 Page 2 of 2

FUCHS LUBRICANTS (UK) plc New Century Street, Hanley Stoke-on-Trent, Staffordshire, ST1 5HU Phone +44 (0) 1782 203700 Fax +44 (0) 1782 202073 contact- uk@fuchs.com

