



Lubricants for
MERCEDES-BENZ
Passenger Cars



It's. Your. Car.

Contact:

[Redacted contact information box]



FUCHS LUBRICANTS CO.
17050 Lathrop Ave.
Harvey, IL 60426
United States
Phone + 1 708-333-8900
E-mail inquiry@fuchs.com
www.fuchs.com/us

This brochure is accurate in information to the FUCHS Lubricants product range at the time of printing. FUCHS Lubricants reserves the right to make changes at any time without notice. Details also available from your FUCHS Lubricants representative. Copyright FUCHS Lubricants USA. September 2018.

09/18 1.0



The Original Oil.

FUCHS supplies to and develops hand in hand with the major German automotive manufacturers. Our innovative power, development competence and product quality are award winning.

TECHNOLOGY THAT PAYS BACK.

www.fuchs.com/us

**VOLKSWAGEN GLOBAL GROUP AWARD
DAIMLER SUPPLIER AWARD
ZF SUPPLIER AWARD**



TTAN Motor Oils

MERCEDES-BENZ	Main Specifications
MB 229.6	Specification for gasoline engines (M270, M274, M276) with increased fuel efficiency (based on but more stringent than ACEA A5/B5). No reverse compatibility with earlier specifications.
MB 229.5	Specification for gasoline engines with extended oil change intervals, low pollution. Reverse compatibility with MB 229.3.
MB 229.3	Specification with similar demands as 229.1 but with extended oil change intervals.
MB 229.52	Specification for diesel Bluetec engines (OM 642). Highest requirements on oxidation stability and fuel economy. Reverse compatibility with MB 229.31 and 229.51.
MB 229.51	Specification for diesel engines with particulate filters and extended oil change intervals. Reverse compatibility with MB 229.31.
MB 229.31	Specification for diesel engines with particulate filters.



TTAN Supersyn LONGLIFE

SAE 5W-40

Ultra high performance fuel-economy engine oil. For very good engine cleanliness and good cold start performance. Suitable for passenger cars with or without extended service intervals.

Specifications	Approvals	Recommendations
API SN	MB 229.5	FORD WSS-M2C937-A
ACEA A3/B4	BMW LONGLIFE-01	
	PORSCHE A40	
	VW 502 00 / 505 00	



TTAN GT1 PRO FLEX

SAE 5W-30

Premium performance motor oil with XTL® Technology for optimum cold start ability and outstanding performance reserves. For modern passenger cars with diesel particulate filters. For extended service intervals.

Specifications	Approvals	Recommendations
API SN	MB 229.51 & 229.52	FIAT 9.55535-S3
ACEA C3	BMW LONGLIFE-04	GM-LL-A-025
	VW 502 00 / 505 00 / 505 01	GM-LL-B-025
	GM Dexos2™	



TTAN GT1 PRO 229.6

SAE 5W-30

Premium performance extreme fuel-economy motor oil with XTL® Technology. Specially designed for Mercedes gasoline vehicles. Optimum cold starting behavior, lower oil consumption and minimized exhaust emissions.

Specifications	Approvals	Recommendations
ACEA A5/B5	MB 229.6	-



TTAN GT1

SAE 5W-40

Premium performance motor oil with XTL® Technology for optimum cold start ability and outstanding performance reserves. For modern passenger cars and light commercial vehicles with or without extended service intervals.

Specifications	Approvals	Recommendations
API SN	MB 226.5 & 229.31	FIAT 9.55535-S2
ACEA C3	BMW LONGLIFE-04	
FORD WSS-M2C917-A	GM Dexos2™	
FORD WSS-M2C948-B	PORSCHE A40	
-	VW 502 00 / 505 00 / 505 01	

TTAN Transmission Fluids

TTAN ATF 9134 FE

Premium Performance automatic transmission fluid with reduced viscosity, especially developed to further optimize fuel-economy and gearbox efficiency of latest generation Mercedes-Benz 9-speed automatic transmissions. Not downwards compatible with previous MB ATF specifications. Product dyeing: yellow.

Specifications	Approvals	Recommendations
-	MB 236.17	-

TTAN ATF 7134 FE

Premium performance automatic transmission fluid with reduced viscosity, especially developed to further optimize fuel-economy and gearbox efficiency of latest generation Mercedes-Benz 7-speed automatic transmissions. Not downwards compatible with previous MB ATF specifications. Product dyeing: blue.

Specifications	Approvals	Recommendations
-	MB 236.15	-

TTAN ATF 4134

Ultra high performance automatic transmission fluid specially developed to optimize shifting performance of Mercedes automatic transmissions. Product dyeing: red.

Specifications	Approvals	Recommendations
-	MB 236.14	-
	SSANG YONG (MB-automatic transmissions)	

TTAN ATF 4000

Ultra high performance automatic transmission fluid. Licensed according to DEXRON III (H). Improved low-temperature shifting compared to DEXRON II. Product dyeing: red.

Specifications	Approvals	Recommendations
-	MB 236.1	-
	MB 236.9	

TTAN ATF 1

Ultra high performance ATF for use in automatic transmissions in passenger cars as well as commercial vehicles. Product dyeing: none.

Specifications	Approvals	Recommendations
-	-	MB 236.11

TTAN CVT

Ultra high performance ATF specially designed for use in CVT-gearboxes using push-belts or transmission chains made of steel. Product dyeing: none.

Specifications	Approvals	Recommendations
-	MB 236.20	-

TTAN Gear Oils

TTAN SINTOPOID FE

SAE 75W-80

Premium performance axle fluid offering increased gearbox efficiency in passenger cars due to low viscosity level. Reduces fuel consumption and offers the best properties at low temperatures. Suitable as fill-for-life fluid according to manufacturer.

Specifications	Approvals	Recommendations
API GL-5	MB 235.7	MB 239.71
	MB 235.74	MB 239.72

TTAN SUPERGEAR MC 80W-90

SAE 80W-90

Super high performance gear oil based on MC synthesis for extended oil change intervals.

Specifications	Approvals	Recommendations
API GL-4/GL-5	MB 235.0	-

MAINTAIN Coolants

MAINTAIN FRICOFIN

Super high performance coolant additive based on monoethylene glycol. Free of nitrite, amine and phosphate. Product dyeing: blue-green.

Specifications	Approvals	Recommendations
-	MB 325.0	-

MAINTAIN FRICOFIN LL

Premium performance coolant additive based on monoethylene glycol. Free of nitrite, amine, phosphate and silicates. Product dyeing: orange.

Specifications	Approvals	Recommendations
-	MB 325.3	-